

Overview

Models

| | |
|--|--------|
| HP VCX Enterprise Branch Communications MIM Module | JE254A |
| HP MSR 30-40 Router with VCX Enterprise Branch Communications MIM Module | JD023A |
| HP MSR 30-16 Router with VCX Enterprise Branch Communications MIM Module | JD024A |

Key features

- Economical VoIP bundles with enterprise WAN router
- Local IP telephony and messaging capabilities
- Full-featured survivability for WAN failures
- Voice, video, IM collaboration, MS Lync interface
- Centralized management capabilities

Product overview

HP VCX Enterprise Branch Communications MIM series provides cost-effective, carrier-class VoIP services to HP VCX V7000 unified communication series branch offices with up to 100 users. Designed to seamlessly integrate within HP A-MSR 30 series WAN routers, the VCX Enterprise Branch MIM leverages MSR modularity to provide a single network solution by delivering a comprehensive suite of integral WAN, LAN, security, wireless and voice interfaces, including Microsoft® OCS/Lync and Exchange UM connectivity. Utilizing the VCX's remote management capabilities, the VCX Enterprise Branch MIM can be distributed across many sites and efficiently administered from any network location. In the event of a catastrophic WAN failure that isolates a branch from central servers, VCX Enterprise Branch MIM delivers full-featured survivability so that your vital business operations function without incident.

Features and benefits

Quality of Service (QoS)

- **Echo cancellation:** automatically adjusts and removes echo from a telephone call
- **Voice activity detection:** the proprietary algorithm is designed to reduce/filter background noise
- **Comfort noise generation:** provides low audible artificial background noise to improve VoIP communications
- **802.1p/Q VLAN tagging:** delivers data to devices based on the priority and type of traffic; supports IEEE 802.1Q

Resiliency and high availability

- **Enhanced high availability:** enterprise branch communications systems provide geographic survivability and rapid failover for mission-critical communications; helps ensure high availability with a carrier-class architecture and distributed applications to reduce the impact of a WAN failure
- **Optional redundant power supply:** provides seamless business continuity and data protection

Configuration

- **Media gateway support:** streamlines migration to IP communications and provides PSTN connectivity with a full range of either integrated or standalone VoIP gateways
- **Scheduled backups:** System Administration Web interface provides the ability to schedule static and reoccurring full system backups

Integration

- **Converged IP telephony and data:** seamlessly integrate the VCX Enterprise Branch MIM (multifunction interface module) into an HP A-MSR 30 series Power over Ethernet (PoE) or non-PoE router to deliver enterprise-class routing and telephony functionality

Investment protection

-



Overview

- **All-in-one solution:** decreases capital and operating expenses and increases network freedom and flexibility by integrating a comprehensive suite of available telephony, routing, switching, and security interfaces and features—all in the same box
- **Analog phone support:** leverages existing investment in analog phones while implementing a full set of PBX features

Ease of use

- **LDAP synchronization with Microsoft Active Directory, IBM Lotus Domino, and Linux OpenLDAP:** easily integrate, filter, and synchronize employee contact information, thereby simplifying administration and providing reliable connections based on the most current user information
- **Easy to use:** GUI-driven central management and configuration

Scalability

- **Supported devices:** let you pay as you grow up to 100 devices

Additional information

- **Optional mobility for telecommuters:** optional HP VCX IP Telecommuting series provides remote users with the full benefit of their corporate IP telephony systems without compromising security
- **Optional multimedia conference bridge:** when businesses require a dense conferencing system to reduce the overhead and the cost of expensive third-party conferencing products, the HP VCX V7000 IP Conferencing series provides capabilities that include host and participant Web-based conference controls, instant and emergency conferences with automatic dial-out options, scheduled and meet-me restricted conferences (requires participant passcode), peer-to-peer and one-to-many conferences, and more
- **Optional network management:** uses the HP Intelligent Management Center (IMC) and Voice Services Manager (VSM) to configure, monitor, and enhance the performance of media servers, gateways, and endpoints; to monitor VoIP traffic; and to control voice network quality; enhancements for IMC VSM include MOS scoring and packet loss notification MIB changes; the VCX license MIBs support IMC

Product architecture

- **Integrated VCX V7000 Unified Communications series branch solution:** is an economical, high-availability IP telephony platform that delivers carrier-class VCX V7000 Unified Communications series SIP-based services to branch sites, enabling full features/functionality in case of a WAN failure; the same feature set and administration interfaces apply to all VCX platforms, including region and branch
- **Multisite architecture:** a highly flexible architecture eliminates the dependency on any single component for unprecedented resiliency and end-to-end survivability; allows you to use Web-based centralized administration, global directory, and global voicemail to seamlessly link VCX systems together to scale your IP-PBX network as your business grows
- **Standards-based IP-PBX:** supports standard PBX and advanced telephony and messaging features based on the IETF Session Initiation Protocol (SIP) standards; supports third-party SIP-based applications and devices
- **Integrated server:** IP telephony and IP messaging modules run on Linux OS
- **Direct SIP integration with Microsoft OCS/Lync and Exchange UM:** VCX direct SIP integration with Microsoft OCS/Lync allows VCX phones/clients to call and have basic features with phones/clients connected to OCS/Lync; OCS/Lync has access to VCX IP-PBX phones, clients, and gateways; VCX supports direct SIP integration with Office Communication Server 2007, Office Communication Server 2007 R2, and Microsoft Lync Server 2010

User productivity

- **Unified communications:** increases employee collaboration through the audio, video, instant messaging, file sharing, and presence capabilities within the HP Desktop Communicator; extends the Microsoft environment with HP Desktop Communicator Outlook Edition add-on to enable click-to-call/conference via Microsoft Outlook, to capture and retrieve call notes with Microsoft Journal, and to perform desktop call recording; HP VCX is fully integrated with Lotus Sametime
- **Unified messaging:** consolidates users' voicemail, email, and faxes into a single inbox for flexible, location-independent retrieval and management; schedules appropriate times when messages are delivered; sends voicemails to individuals or groups using extensive and easy-to-maintain distribution lists; sets up find me/follow

Overview

me services to conveniently manage one's own access to help ensure that important calls are not missed

- **Lotus Domino/Sametime 8.5 support:** Sametime 8.5 can be deployed using a Sametime System Console and new meeting server functionality; VCX provides two packages for Sametime 8.5; can be deployed on Sametime Community Server ("classic" to pre-8.5) or on Sametime Media Manager (for 8.5) using the system console

Warranty and support

- **1-year warranty:** with advance replacement and 30-calendar-day delivery (available in most countries)
- **Electronic and telephone support:** limited electronic and telephone support is available from HP; refer to: www.hp.com/networking/warranty for details on the support provided and the period during which support is available
- **Software releases:** refer to: www.hp.com/networking/warranty for details on the software releases provided and the period during which software releases are available for your product(s)

Technical Specifications

HP VCX Enterprise Branch Communications MIM Module (JE254A)

| | | |
|---------------------------------|---|--|
| Ports | 1 RJ-45 autosensing 10/100 port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full | |
| | 2 USB 2.0 | |
| Physical characteristics | Dimensions | 8.27(d) x 5.91(w) x 1.57(h) in. (21 x 15 x 4 cm) (1U height) |
| | Weight | 2.43 lb. (1.1 kg) |
| Memory and processor | Module | Intel® Celeron® @ 600 MHz, 1 GB DDR SODIMM; storage: 160 GB HD |
| Mounting | VCX Enterprise Branch Communications module slides into an HP A-MSR 30 series router MIM slot | |
| Environment | Operating temperature | 41°F to 104°F (5°C to 40°C) |
| | Operating relative humidity | 10% to 80% |
| | Nonoperating/Storage temperature | -40°F to 158°F (-40°C to 70°C) |
| Management Services | IMC - Intelligent Management Center; Web browser; SNMP Manager; Telnet; HTTPS Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office. | |

HP MSR 30-40 Router with VCX Enterprise Branch Communications MIM Module (JD023A)

| | | |
|-----------------------------------|--|--|
| Ports | 1 RJ-45 autosensing 10/100 port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full | |
| | 4 USB 2.0 | |
| | 2 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only | |
| | 2 SFP | |
| | 1 Compact Flash port | |
| Physical characteristics | Dimensions | 16.62(d) x 17.4(w) x 3.47(h) in. (42.21 x 44.2 x 8.81 cm) (2U height) |
| | Weight | 28.66 lb. (13.0 kg) including VCX Enterprise Branch Communications MIM |
| Mounting | VCX Enterprise Branch Communications module slides into an A-MSR 30 series router MIM slot; the router mounts into an EIA-standard 19 inch telco rack or cabinet or table top (hardware included) | |
| Environment | Operating temperature | 41°F to 104°F (5°C to 40°C) |
| | Operating relative humidity | 10% to 80% |
| | Nonoperating/Storage temperature | -40°F to 158°F (-40°C to 70°C) |
| Electrical characteristics | Voltage | 100-240 VAC |
| | Frequency | 50/60 Hz |
| Management | IMC - Intelligent Management Center; Web browser; SNMP Manager; Telnet; HTTPS | |
| Notes | MSR 30-40 integrated voice gateway options: <ul style="list-style-type: none"> • Supports up to a maximum of 24 analog voice ports • Supports up to a maximum of 16 ISDN voice ports • Supports up to a maximum of 5 E1 or T1 digital voice spans Bundle includes MSR 30-40 router with VCX Enterprise Branch Communications MIM module | |
| Services | 3-year, parts only, global next-day advance exchange (UX150E) | |

Technical Specifications

- 3-year, 4-hour onsite, 13x5 coverage for hardware (UX151E)
- 3-year, 4-hour onsite, 24x7 coverage for hardware (UX154E)
- 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UX157E)
- 3-year, 24x7 SW phone support, software updates (UX160E)
- 4-year, 4-hour onsite, 13x5 coverage for hardware (UX152E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware (UX155E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UX158E)
- 4-year, 24x7 SW phone support, software updates (UX161E)
- 5-year, 4-hour onsite, 13x5 coverage for hardware (UX153E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware (UX156E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UX159E)
- 5-year, 24x7 SW phone support, software updates (UX162E)
- 3 Yr 6 hr Call-to-Repair Onsite (UX163E)
- 4 Yr 6 hr Call-to-Repair Onsite (UX164E)
- 5 Yr 6 hr Call-to-Repair Onsite (UX165E)

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP MSR 30-16 Router with VCX Enterprise Branch Communications MIM Module (JD024A)

| | |
|-----------------------------------|---|
| Ports | 3 RJ-45 autosensing 10/100 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full |
| | 3 USB 2.0 |
| | 1 Compact Flash port |
| Physical characteristics | Dimensions 17.39(d) x 17.4(w) x 1.74(h) in. (44.17 x 44.2 x 4.42 cm) (1U height) |
| | Weight 15.65 lb. (7.1 kg) including VCX Enterprise Branch Communications MIM |
| Mounting | VCX Enterprise Branch Communications module slides into an A-MSR 30 series router MIM slot; the router mounts into an EIA-standard 19 inch telco rack or cabinet or table top (hardware included) |
| Environment | Operating temperature 41°F to 104°F (5°C to 40°C) |
| | Operating relative humidity 10% to 80% |
| | Nonoperating/Storage temperature -40°F to 158°F (-40°C to 70°C) |
| Electrical characteristics | Voltage 100-240 VAC |
| | Frequency 50/60 Hz |
| Management | IMC - Intelligent Management Center; Web browser; SNMP Manager; Telnet; HTTPS |
| Notes | MSR 30-16 integrated voice gateway options: <ul style="list-style-type: none"> • Supports up to a maximum of 12 analog voice ports • Supports up to a maximum of 8 ISDN voice ports • Supports up to a maximum of 4 E1 or T1 digital voice spans Bundle includes MSR 30-16 router with VCX Enterprise Branch Communications MIM module |
| Services | 3-year, parts only, global next-day advance exchange (UX150E) |
| | 3-year, 4-hour onsite, 13x5 coverage for hardware (UX151E) |
| | 3-year, 4-hour onsite, 24x7 coverage for hardware (UX154E) |
| | 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UX157E) |
| | 3-year, 24x7 SW phone support, software updates (UX160E) |
| | 4-year, 4-hour onsite, 13x5 coverage for hardware (UX152E) |

Technical Specifications

- 4-year, 4-hour onsite, 24x7 coverage for hardware (UX155E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UX158E)
- 4-year, 24x7 SW phone support, software updates (UX161E)
- 5-year, 4-hour onsite, 13x5 coverage for hardware (UX153E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware (UX156E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UX159E)
- 5-year, 24x7 SW phone support, software updates (UX162E)
- 3 Yr 6 hr Call-to-Repair Onsite (UX163E)
- 4 Yr 6 hr Call-to-Repair Onsite (UX164E)
- 5 Yr 6 hr Call-to-Repair Onsite (UX165E)

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessories

HP VCX Enterprise Branch Communications MIM on MSR Series accessories

| | |
|---|----------|
| Cables | |
| HP X260 E1 BNC 75 ohm 3m Router Cable | JD175A |
| HP X260 E1 RJ45 3m Router Cable | JD509A |
| HP X260 E1 RJ45 BNC 75-120 ohm Conversion Router Cable | JD511A |
| HP X260 E1 BNC 20m Router Cable | JD514A |
| HP X260 E1 BNC 75 ohm 40m Router Cable | JD516A |
| HP X260 E1 RJ45 20m Router Cable | JD517A |
| HP X260 T1 Router Cable | JD518A |
| Power Supply | |
| HP A-RPS800 Redundant Power System | JD183A |
| License | |
| HP VCX V6100/Enterprise Branch Communications MIM IP Telephony and IP Messaging 9.x License E-LTU | JE420BAE |
| Routers | |
| HP A-MSR30-16 Router | JF233A |
| HP A-MSR30-16 PoE Router | JF234A |
| HP A-MSR30-20 Router | JF284A |
| HP A-MSR30-20 PoE Router | JF802A |
| HP A-MSR30-40 Router | JF229A |
| HP A-MSR30-40 PoE Router | JF803A |
| HP A-MSR30-60 Router | JF230A |
| HP A-MSR30-60 PoE Router | JF804A |
| Router Modules | |
| HP A-MSR 24-Channel Voice Processing Module | JD599A |
| HP A-MSR 32-Channel Voice Processing Module | JD598A |
| HP A-MSR Voice Co-processing Module | JD610A |
| HP A-MSR 1-port FXO SIC Module | JD559A |
| HP A-MSR 2-port FXO SIC Module | JD558A |
| HP A-MSR 1-port FXS SIC Module | JD561A |
| HP A-MSR 2-port FXS SIC Module | JD560A |
| HP A-MSR 2-port FXS/1-port FXO SIC Module | JD632A |
| HP A-MSR 2-port ISDN-S/T Voice SIC Module | JF821A |
| HP A-MSR 1-port E1 Voice SIC Module | JD575A |
| HP A-MSR 1-port T1 Voice SIC Module | JD576A |
| HP A-MSR 4-port E/M MIM Module | JD539A |
| HP A-MSR 2-port FXO MIM Module | JD543A |
| HP A-MSR 4-port FXO MIM Module | JD542A |
| HP A-MSR 4-port FXS MIM Module | JD553A |
| HP A-MSR 16-port FXS MIM Module | JF822A |
| HP A-MSR 4-port ISDN-S/T Voice MIM Module | JF837A |
| HP A-MSR 1-port E1 Voice MIM Module | JD565A |
| HP A-MSR 1-port T1 Voice MIM Module | JD566A |
| HP A-MSR 2-port E1 Voice MIM Module | JD567A |
| HP A-MSR 2-port T1 Voice MIM Module | JD568A |
| Power cords | |
| HP X290 1m RPS Cable | JD637A |

Accessory Product Details

NOTE: Details are not available for all accessories. The following specifications were available at the time of publication.

HP A-MSR30-16 Multi-Service Router (JF233A)

| | |
|-----------------------------------|---|
| Ports | 4 SIC slots 1 MIM module slot 2 auto-sensing 10/100 WAN ports (IEEE 802.3 Type 10Base-T, IEEE 802.3u Type 100Base-TX); Duplex: half or full |
| Physical characteristics | Dimensions 17.39(d) x 17.4(w) x 1.74(h) in. (44.18 x 44.2 x 4.42 cm) (1U height) Weight 13.23 lb. (6 kg) |
| Memory and processor | Processor RISC @ 400 MHz, 256 MB DDR SDRAM, 256 MB compact flash |
| Mounting | Mounts in an EIA standard 19-in. rack |
| Performance | Throughput 240 Kpps (64-byte packets) Routing table size 30,000 entries |
| Environment | Operating temperature 32°F to 104°F (0°C to 40°C) Operating relative humidity 5% to 90%, non-condensing Non-operating/Storage temperature -40°F to 158°F (-40°C to 70°C) Non-operating/Storage relative humidity 5% to 90%, non-condensing |
| Electrical characteristics | Maximum heat dissipation 341 BTU/hr (359.76 kJ/hr) Voltage 100-120 / 200-240 VAC Maximum power rating 100 W Frequency 50 / 60 Hz Notes Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. |
| Safety | UL 60950-1; AS/NZS 60950; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1-03; EN 60950-1/A11; FDA 21 CFR Subchapter J |
| Emissions | EN 55022 Class A; ICES-003 Class A; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; AS/NZS CISPR22 Class A; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A; EN 55024:1998+ A1:2001 + A2:2003; EN 61000-4-11:2004; EN 61000-4-8:2001 |
| Telecom Management | FCC part 68 IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager; Telnet; RMON1; FTP; IEEE 802.3 Ethernet MIB |
| Services | 3-year, parts only, global next-day advance exchange (UX150E) 3-year, 4-hour onsite, 13x5 coverage for hardware (UX151E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UX154E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UX157E) 3-year, 24x7 SW phone support, software updates (UX160E) 4-year, 4-hour onsite, 13x5 coverage for hardware (UX152E) 4-year, 4-hour onsite, 24x7 coverage for hardware (UX155E) 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UX158E) 4-year, 24x7 SW phone support, software updates (UX161E) 5-year, 4-hour onsite, 13x5 coverage for hardware (UX153E) |

Accessory Product Details

- 5-year, 4-hour onsite, 24x7 coverage for hardware (UX156E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UX159E)
- 5-year, 24x7 SW phone support, software updates (UX162E)
- 3 Yr 6 hr Call-to-Repair Onsite (UX163E)
- 4 Yr 6 hr Call-to-Repair Onsite (UX164E)
- 5 Yr 6 hr Call-to-Repair Onsite (UX165E)

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Standards and protocols

(applies to all products in series)

BGP

- RFC 1163 Border Gateway Protocol (BGP)
- RFC 1267 Border Gateway Protocol 3 (BGP-3)
- RFC 1657 Definitions of Managed Objects for BGPv4
- RFC 1771 BGPv4
- RFC 1772 Application of the BGP
- RFC 1773 Experience with the BGP-4 Protocol
- RFC 1774 BGP-4 Protocol Analysis
- RFC 1965 BGP4 confederations
- RFC 1997 BGP Communities Attribute
- RFC 1998 PPP Gandalf FZA Compression Protocol
- RFC 2385 BGP Session Protection via TCP MD5
- RFC 2439 BGP Route Flap Damping

Device management

- RFC 1305 NTPv3
- RFC 1945 Hypertext Transfer Protocol -- HTTP/1.0
- RFC 2271 FrameWork
- RFC 2452 MIB for TCP6
- RFC 2454 MIB for UDP6

General protocols

- IEEE 802.1D MAC Bridges
- IEEE 802.1p Priority
- IEEE 802.1Q VLANs
- IEEE 802.1s Multiple Spanning Trees
- IEEE 802.1w Rapid Reconfiguration of Spanning Tree
- RFC 768 UDP
- RFC 783 TFTP Protocol (revision 2)
- RFC 791 IP
- RFC 792 ICMP
- RFC 793 TCP
- RFC 826 ARP
- RFC 854 TELNET
- RFC 855 Telnet Option Specification
- RFC 856 TELNET
- RFC 858 Telnet Suppress Go Ahead Option
- RFC 894 IP over Ethernet
- RFC 925 Multi-LAN Address Resolution
- RFC 950 Internet Standard Subnetting Procedure
- RFC 959 File Transfer Protocol (FTP)

- RFC 3032 MPLS Label Stack Encoding
- RFC 3036 LDP Specification
- RFC 3046 DHCP Relay Agent Information Option
- RFC 3063 MPLS Loop Prevention Mechanism
- RFC 3065 Support AS confederation
- RFC 3137 OSPF Stub Router Advertisement
- RFC 3209 RSVP-TE Extensions to RSVP for LSP Tunnels
- RFC 3210 Applicability Statement for Extensions to RSVP for LSP-Tunnels
- RFC 3212 Constraint-Based LSP setup using LDP (CR-LDP)
- RFC 3214 LSP Modification Using CR-LDP
- RFC 3215 LDP State Machine
- RFC 3246 Expedited Forwarding PHB
- RFC 3268 Advanced Encryption Standard (AES) Ciphersuites for Transport Layer Security (TLS)
- RFC 3277 IS-IS Transient Blackhole Avoidance
- RFC 3279 Algorithms and Identifiers for the Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
- RFC 3280 Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
- RFC 3392 Support BGP capabilities advertisement
- RFC 3479 Fault Tolerance for the Label Distribution Protocol (LDP)
- RFC 3564 Requirements for Support of Differentiated Services-aware MPLS Traffic Engineering
- RFC 3602 The AES-CBC Cipher Algorithm and Its Use with IPsec
- RFC 3706 A Traffic-Based Method of Detecting Dead Internet Key Exchange (IKE) Peers
- RFC 3784 ISIS TE support
- RFC 3786 Extending the Number of IS-IS LSP Fragments Beyond the 256 Limit
- RFC 3811 Definitions of Textual Conventions

Accessory Product Details

| | |
|--|--|
| RFC 1006 ISO transport services on top of the TCP: Version 3 | (TCs) for Multiprotocol Label Switching (MPLS) Management |
| RFC 1027 Proxy ARP | RFC 3812 Multiprotocol Label Switching (MPLS) Traffic Engineering (TE) Management Information Base (MIB) |
| RFC 1034 Domain Concepts and Facilities | RFC 3847 Restart signaling for IS-IS |
| RFC 1035 Domain Implementation and Specification | |
| RFC 1042 IP Datagrams | |
| RFC 1058 RIPv1 | |
| RFC 1071 Computing the Internet Checksum | IP multicast |
| RFC 1091 Telnet Terminal-Type Option | RFC 1112 IGMP |
| RFC 1122 Host Requirements | RFC 2236 IGMPv2 |
| RFC 1141 Incremental updating of the Internet checksum | RFC 2283 Multiprotocol Extensions for BGP-4 |
| RFC 1142 OSI IS-IS Intra-domain Routing Protocol | RFC 2362 PIM Sparse Mode |
| RFC 1144 Compressing TCP/IP headers for low-speed serial links | RFC 2934 Protocol Independent Multicast MIB for |
| RFC 1195 OSI ISIS for IP and Dual Environments | |
| RFC 1256 ICMP Router Discovery Protocol (IRDP) | IPv4 |
| RFC 1293 Inverse Address Resolution Protocol | RFC 3376 IGMPv3 |
| RFC 1315 Management Information Base for Frame Relay DTEs | IPv6 |
| RFC 1332 The PPP Internet Protocol Control Protocol (IPCP) | RFC 1981 IPv6 Path MTU Discovery |
| RFC 1333 PPP Link Quality Monitoring | RFC 2080 RIPng for IPv6 |
| RFC 1334 PPP Authentication Protocols (PAP) | RFC 2292 Advanced Sockets API for IPv6 |
| RFC 1349 Type of Service | RFC 2373 IPv6 Addressing Architecture |
| RFC 1350 TFTP Protocol (revision 2) | RFC 2460 IPv6 Specification |
| RFC 1377 The PPP OSI Network Layer Control Protocol (OSINLCP) | RFC 2461 IPv6 Neighbor Discovery |
| RFC 1381 SNMP MIB Extension for X.25 LAPB | RFC 2462 IPv6 Stateless Address Auto-configuration |
| RFC 1471 The Definitions of Managed Objects for the Link Control Protocol of the Point-to-Point Protocol | RFC 2464 Transmission of IPv6 over Ethernet Networks |
| RFC 1472 The Definitions of Managed Objects for the Security Protocols of the Point-to-Point Protocol | RFC 2472 IP Version 6 over PPP |
| RFC 1490 Multiprotocol Interconnect over Frame Relay | RFC 2473 Generic Packet Tunneling in IPv6 |
| RFC 1519 CIDR | RFC 2529 Transmission of IPv6 Packets over IPv4 |
| RFC 1534 DHCP/BOOTP Interoperation | RFC 2545 Use of MP-BGP-4 for IPv6 |
| RFC 1542 Clarifications and Extensions for the Bootstrap Protocol | RFC 2553 Basic Socket Interface Extensions for IPv6 |
| RFC 1552 The PPP Internetworking Packet Exchange Control Protocol (IPXCP) | RFC 2740 OSPFv3 for IPv6 |
| RFC 1577 Classical IP and ARP over ATM | RFC 2893 Transition Mechanisms for IPv6 Hosts and Routers |
| RFC 1613 Cisco Systems X.25 over TCP (XOT) | RFC 3056 Connection of IPv6 Domains via IPv4 Clouds |
| RFC 1624 Incremental Internet Checksum | RFC 3513 IPv6 Addressing Architecture |
| RFC 1631 NAT | RFC 3596 DNS Extension for IPv6 |
| | MIBs |
| | RFC 1213 MIB II |
| | RFC 1229 Interface MIB Extensions |
| | RFC 1286 Bridge MIB |
| | RFC 1493 Bridge MIB |
| | RFC 1573 SNMP MIB II |
| | RFC 1724 RIPv2 MIB |
| | RFC 1757 Remote Network Monitoring MIB |
| | RFC 1850 OSPFv2 MIB |
| | RFC 2011 SNMPv2 MIB for IP |
| | RFC 2012 SNMPv2 MIB for TCP |
| | RFC 2013 SNMPv2 MIB for UDP |

Accessory Product Details

| | |
|--|--|
| Ethernet (PPPoE) | Protocol |
| RFC 2644 Directed Broadcast Control | RFC 2865 RADIUS Authentication |
| RFC 2661 L2TP | RFC 2866 RADIUS Accounting |
| RFC 2663 NAT Terminology and Considerations | RFC 3567 Intermediate System (IS) to IS |
| RFC 2684 Multiprotocol Encapsulation over ATM | Cryptographic Authentication |
| Adaptation Layer 5 | VPN |
| RFC 2694 DNS extensions to Network Address Translators (DNS_ALG) | RFC 2403 - HMAC-MD5-96 |
| RFC 2702 Requirements for Traffic Engineering Over MPLS | RFC 2404 - HMAC-SHA1-96 |
| RFC 2747 RSVP Cryptographic Authentication | RFC 2405 - DES-CBC Cipher algorithm |
| RFC 2763 Dynamic Name-to-System ID mapping support | RFC 2547 BGP/MPLS VPNs |
| RFC 2765 Stateless IP/ICMP Translation Algorithm (SIIT) | RFC 2796 BGP Route Reflection - An Alternative to Full Mesh IBGP |
| RFC 2766 Network Address Translation - Protocol | RFC 2842 Capabilities Advertisement with BGP-4 |
| Translation (NAT-PT) | RFC 2858 Multiprotocol Extensions for BGP-4 |
| RFC 2784 Generic Routing Encapsulation (GRE) | RFC 2918 Route Refresh Capability for BGP-4 |
| RFC 2787 Definitions of Managed Objects for VRRP | RFC 3107 Carrying Label Information in BGP-4 |
| RFC 2961 RSVP Refresh Overhead Reduction Extensions | IPsec |
| RFC 2966 Domain-wide Prefix Distribution with Two-Level IS-IS | RFC 1828 IP Authentication using Keyed MD5 |
| RFC 2973 IS-IS Mesh Groups | RFC 2401 IP Security Architecture |
| RFC 2993 Architectural Implications of NAT | RFC 2402 IP Authentication Header |
| RFC 3022 Traditional IP Network Address Translator (Traditional NAT) | RFC 2406 IP Encapsulating Security Payload |
| RFC 3027 Protocol Complications with the IP Network Address Translator | RFC 2407 - Domain of interpretation |
| RFC 3031 Multiprotocol Label Switching Architecture | RFC 2410 - The NULL Encryption Algorithm and its use with IPsec |
| | RFC 2411 IP Security Document Roadmap |
| | RFC 2412 - OAKLEY |
| | RFC 2865 - Remote Authentication Dial In User Service (RADIUS) |

HP A-MSR30-16 PoE Multi-Service Router (JF234A)

| | |
|---------------------------------|---|
| Ports | 4 SIC slots |
| | 1 MIM module slot |
| | 2 auto-sensing 10/100 WAN ports (IEEE 802.3 Type 10Base-T, IEEE 802.3u Type 100Base-TX); Duplex: half or full |
| Physical characteristics | Dimensions 17.39(d) x 17.4(w) x 1.74(h) in. (44.18 x 44.2 x 4.42 cm) (1U height) |
| | Weight 13.23 lb. (6 kg) |
| Memory and processor | Processor RISC @ 400 MHz, 256 MB DDR SDRAM, 256 MB compact flash |
| Mounting | Mounts in an EIA standard 19-in. rack |
| Performance | Throughput 240 Kpps (64-byte packets) |
| | Routing table size 30,000 entries |
| Environment | Operating temperature 32°F to 104°F (0°C to 40°C) |
| | Operating relative humidity 5% to 90%, non-condensing |
| | Non-operating/Storage temperature -40°F to 158°F (-40°C to 70°C) |



Accessory Product Details

| | | |
|---|---|--|
| | Non-operating/Storage relative humidity | 5% to 90% |
| Electrical characteristics | Maximum heat dissipation | 341 BTU/hr (359.76 kJ/hr) |
| | Voltage | 100-120 / 200-240 VAC |
| | Maximum power rating | 100 W |
| | PoE power | 150 W |
| | Frequency | 50 / 60 Hz |
| | Notes | Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. PoE power is the power supplied by the internal power supply. It is dependent on the type and quantity of power supplies and may be supplemented with the use of an external power supply (EPS). |
| | Safety | UL 60950-1; AS/NZS 60950; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1-03; EN 60950-1/A11; FDA 21 CFR Subchapter J |
| Emissions | EN 55022 Class A; ICES-003 Class A; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; AS/NZS CISPR22 Class A; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A; EN 55024:1998+ A1:2001 + A2:2003; EN 61000-4-11:2004; EN 61000-4-8:2001 | |
| Telecom Management | FCC part 68 IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager; Telnet; RMON1; FTP; IEEE 802.3 Ethernet MIB | |
| Services | 3-year, parts only, global next-day advance exchange (UX150E) | |
| | 3-year, 4-hour onsite, 13x5 coverage for hardware (UX151E) | |
| | 3-year, 4-hour onsite, 24x7 coverage for hardware (UX154E) | |
| | 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UX157E) | |
| | 3-year, 24x7 SW phone support, software updates (UX160E) | |
| | 4-year, 4-hour onsite, 13x5 coverage for hardware (UX152E) | |
| | 4-year, 4-hour onsite, 24x7 coverage for hardware (UX155E) | |
| | 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UX158E) | |
| | 4-year, 24x7 SW phone support, software updates (UX161E) | |
| | 5-year, 4-hour onsite, 13x5 coverage for hardware (UX153E) | |
| | 5-year, 4-hour onsite, 24x7 coverage for hardware (UX156E) | |
| | 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UX159E) | |
| | 5-year, 24x7 SW phone support, software updates (UX162E) | |
| 3 Yr 6 hr Call-to-Repair Onsite (UX163E) | | |
| 4 Yr 6 hr Call-to-Repair Onsite (UX164E) | | |
| 5 Yr 6 hr Call-to-Repair Onsite (UX165E) | | |
| | Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office. | |
| Standards and protocols (applies to all products in series) | BGP | RFC 3032 MPLS Label Stack Encoding |
| | RFC 1163 Border Gateway Protocol (BGP) | RFC 3036 LDP Specification |
| | RFC 1267 Border Gateway Protocol 3 (BGP-3) | RFC 3046 DHCP Relay Agent Information Option |
| | RFC 1657 Definitions of Managed Objects for BGPv4 | RFC 3063 MPLS Loop Prevention Mechanism |
| | RFC 1771 BGPv4 | RFC 3065 Support AS confederation |
| | RFC 1772 Application of the BGP | RFC 3137 OSPF Stub Router Advertisement |
| | RFC 1773 Experience with the BGP-4 Protocol | RFC 3209 RSVP-TE Extensions to RSVP for |

Accessory Product Details

RFC 1774 BGP-4 Protocol Analysis
RFC 1965 BGP4 confederations
RFC 1997 BGP Communities Attribute
RFC 1998 PPP Gandalf FZA Compression Protocol
RFC 2385 BGP Session Protection via TCP MD5
RFC 2439 BGP Route Flap Damping

Device management

RFC 1305 NTPv3
RFC 1945 Hypertext Transfer Protocol -- HTTP/1.0
RFC 2271 FrameWork
RFC 2452 MIB for TCP6
RFC 2454 MIB for UDP6

General protocols

IEEE 802.1D MAC Bridges
IEEE 802.1p Priority
IEEE 802.1Q VLANs
IEEE 802.1s Multiple Spanning Trees
IEEE 802.1w Rapid Reconfiguration of Spanning Tree
RFC 768 UDP
RFC 783 TFTP Protocol (revision 2)
RFC 791 IP
RFC 792 ICMP
RFC 793 TCP
RFC 826 ARP
RFC 854 TELNET
RFC 855 Telnet Option Specification
RFC 856 TELNET
RFC 858 Telnet Suppress Go Ahead Option
RFC 894 IP over Ethernet
RFC 925 Multi-LAN Address Resolution
RFC 950 Internet Standard Subnetting Procedure
RFC 959 File Transfer Protocol (FTP)
RFC 1006 ISO transport services on top of the TCP:
Version 3
RFC 1027 Proxy ARP
RFC 1034 Domain Concepts and Facilities
RFC 1035 Domain Implementation and Specification
RFC 1042 IP Datagrams
RFC 1058 RIPv1
RFC 1071 Computing the Internet Checksum
RFC 1091 Telnet Terminal-Type Option
RFC 1122 Host Requirements
RFC 1141 Incremental updating of the Internet checksum
RFC 1142 OSI IS-IS Intra-domain Routing Protocol
RFC 1144 Compressing TCP/IP headers for low-speed serial links
RFC 1195 OSI ISIS for IP and Dual

LSP
Tunnels
RFC 3210 Applicability Statement for Extensions to
RSVP for LSP-Tunnels
RFC 3212 Constraint-Based LSP setup using LDP
(CR-LDP)
RFC 3214 LSP Modification Using CR-LDP
RFC 3215 LDP State Machine
RFC 3246 Expedited Forwarding PHB
RFC 3268 Advanced Encryption Standard (AES) Ciphersuites for Transport Layer Security (TLS)
RFC 3277 IS-IS Transient Blackhole Avoidance
RFC 3279 Algorithms and Identifiers for the Internet
X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
RFC 3280 Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
RFC 3392 Support BGP capabilities advertisement
RFC 3479 Fault Tolerance for the Label Distribution Protocol (LDP)
RFC 3564 Requirements for Support of Differentiated Services-aware MPLS Traffic Engineering
RFC 3602 The AES-CBC Cipher Algorithm and Its Use with IPsec
RFC 3706 A Traffic-Based Method of Detecting Dead Internet Key Exchange (IKE) Peers
RFC 3784 ISIS TE support
RFC 3786 Extending the Number of IS-IS LSP Fragments Beyond the 256 Limit
RFC 3811 Definitions of Textual Conventions (TCs) for Multiprotocol Label Switching (MPLS) Management
RFC 3812 Multiprotocol Label Switching (MPLS) Traffic Engineering (TE) Management Information Base (MIB)
RFC 3847 Restart signaling for IS-IS

IP multicast

RFC 1112 IGMP
RFC 2236 IGMPv2
RFC 2283 Multiprotocol Extensions for BGP-4
RFC 2362 PIM Sparse Mode
RFC 2934 Protocol Independent Multicast MIB for

IPv4

RFC 3376 IGMPv3

Accessory Product Details

| | |
|--|---|
| Environments | IPv6 |
| RFC 1256 ICMP Router Discovery Protocol (IRDP) | RFC 1981 IPv6 Path MTU Discovery |
| RFC 1293 Inverse Address Resolution Protocol | RFC 2080 RIPng for IPv6 |
| RFC 1315 Management Information Base for Frame | RFC 2292 Advanced Sockets API for IPv6 |
| Relay DTEs | RFC 2373 IPv6 Addressing Architecture |
| RFC 1332 The PPP Internet Protocol Control Protocol (IPCP) | RFC 2460 IPv6 Specification |
| RFC 1333 PPP Link Quality Monitoring | RFC 2461 IPv6 Neighbor Discovery |
| RFC 1334 PPP Authentication Protocols (PAP) | RFC 2462 IPv6 Stateless Address Auto-configuration |
| RFC 1349 Type of Service | RFC 2464 Transmission of IPv6 over Ethernet Networks |
| RFC 1350 TFTP Protocol (revision 2) | RFC 2472 IP Version 6 over PPP |
| RFC 1377 The PPP OSI Network Layer Control Protocol (OSINLCP) | RFC 2473 Generic Packet Tunneling in IPv6 |
| RFC 1381 SNMP MIB Extension for X.25 LAPB | RFC 2529 Transmission of IPv6 Packets over IPv4 |
| RFC 1471 The Definitions of Managed Objects for the Link Control Protocol of the Point-to-Point Protocol | RFC 2545 Use of MP-BGP-4 for IPv6 |
| RFC 1472 The Definitions of Managed Objects for the Security Protocols of the Point-to-Point Protocol | RFC 2553 Basic Socket Interface Extensions for IPv6 |
| RFC 1490 Multiprotocol Interconnect over Frame Relay | RFC 2740 OSPFv3 for IPv6 |
| RFC 1519 CIDR | RFC 2893 Transition Mechanisms for IPv6 Hosts and Routers |
| RFC 1534 DHCP/BOOTP Interoperation | RFC 3056 Connection of IPv6 Domains via IPv4 Clouds |
| RFC 1542 Clarifications and Extensions for the Bootstrap Protocol | RFC 3513 IPv6 Addressing Architecture |
| RFC 1552 The PPP Internetworking Packet Exchange Control Protocol (IPXCP) | RFC 3596 DNS Extension for IPv6 |
| RFC 1577 Classical IP and ARP over ATM | MIBs |
| RFC 1613 Cisco Systems X.25 over TCP (XOT) | RFC 1213 MIB II |
| RFC 1624 Incremental Internet Checksum | RFC 1229 Interface MIB Extensions |
| RFC 1631 NAT | RFC 1286 Bridge MIB |
| RFC 1638 PPP Bridging Control Protocol (BCP) | RFC 1493 Bridge MIB |
| RFC 1661 The Point-to-Point Protocol (PPP) | RFC 1573 SNMP MIB II |
| RFC 1662 PPP in HDLC-like Framing | RFC 1724 RIPv2 MIB |
| RFC 1695 Definitions of Managed Objects for ATM Management Version 8.0 using SMIv2 | RFC 1757 Remote Network Monitoring MIB |
| RFC 1701 Generic Routing Encapsulation | RFC 1850 OSPFv2 MIB |
| RFC 1702 Generic Routing Encapsulation over IPv4 networks | RFC 2011 SNMPv2 MIB for IP |
| RFC 1721 RIP-2 Analysis | RFC 2012 SNMPv2 MIB for TCP |
| RFC 1722 RIP-2 Applicability | RFC 2013 SNMPv2 MIB for UDP |
| RFC 1723 RIP v2 | RFC 2233 Interfaces MIB |
| RFC 1795 Data Link Switching: Switch-to-Switch Protocol AIW DLSw RIG: DLSw Closed Pages, DLSw Standard Version 1 | RFC 2454 IPV6-UDP-MIB |
| RFC 1812 IPv4 Routing | RFC 2465 IPv6 MIB |
| RFC 1829 The ESP DES-CBC Transform | RFC 2466 ICMPv6 MIB |
| | RFC 2618 RADIUS Client MIB |
| | RFC 2620 RADIUS Accounting MIB |
| | RFC 2674 802.1p and IEEE 802.1Q Bridge MIB |
| | RFC 2737 Entity MIB (Version 2) |
| | RFC 2863 The Interfaces Group MIB |
| | RFC 2933 IGMP MIB |
| | RFC 3813 MPLS LSR MIB |
| | Network management |
| | IEEE 802.1D (STP) |
| | RFC 1155 Structure of Management Information |
| | RFC 1157 SNMPv1 |
| | RFC 1905 SNMPv2 Protocol Operations |
| | RFC 2272 SNMPv3 Management Protocol |
| | RFC 2273 SNMPv3 Applications |

Accessory Product Details

| | |
|--|---|
| RFC 1877 PPP Internet Protocol Control Protocol | RFC 2274 USM for SNMPv3 |
| Extensions for Name Server Addresses | RFC 2275 VACM for SNMPv3 |
| RFC 1944 Benchmarking Methodology for Network Interconnect Devices | RFC 2575 SNMPv3 View-based Access Control Model (VACM) |
| RFC 1973 PPP in Frame Relay | RFC 3164 BSD syslog Protocol |
| RFC 1974 PPP Stac LZS Compression Protocol | OSPF |
| RFC 1990 The PPP Multilink Protocol (MP) | RFC 1245 OSPF protocol analysis |
| RFC 1994 PPP Challenge Handshake Authentication Protocol (CHAP) | RFC 1246 Experience with OSPF |
| RFC 2091 Trigger RIP | RFC 1587 OSPF NSSA |
| RFC 2131 DHCP | RFC 1765 OSPF Database Overflow |
| RFC 2132 DHCP Options and BOOTP Vendor Extensions | RFC 1850 OSPFv2 Management Information Base (MIB), traps |
| RFC 2166 APPN Implementer's Workshop Closed | RFC 2328 OSPFv2 |
| Pages Document DLSw v2.0 Enhancements | RFC 2370 OSPF Opaque LSA Option |
| RFC 2205 Resource ReSerVation Protocol (RSVP) - Version 1 Functional Specification | RFC 3101 OSPF NSSA |
| RFC 2280 Routing Policy Specification Language (RPSL) | QoS/CoS |
| RFC 2284 EAP over LAN | IEEE 802.1P (CoS) |
| RFC 2338 VRRP | RFC 2474 DS Field in the IPv4 and IPv6 Headers |
| RFC 2364 PPP Over AAL5 | RFC 2475 DiffServ Architecture |
| RFC 2374 An Aggregatable Global Unicast Address Format | RFC 2597 DiffServ Assured Forwarding (AF) |
| RFC 2451 The ESP CBC-Mode Cipher Algorithms | RFC 2598 DiffServ Expedited Forwarding (EF) |
| RFC 2453 IPv2 | RFC 3168 The Addition of Explicit Congestion Notification (ECN) to IP |
| RFC 2510 Internet X.509 Public Key Infrastructure | Security |
| Certificate Management Protocols | IEEE 802.1X Port Based Network Access Control |
| RFC 2511 Internet X.509 Certificate Request Message Format | RFC 1321 The MD5 Message-Digest Algorithm |
| RFC 2516 A Method for Transmitting PPP Over Ethernet (PPPoE) | RFC 2082 RIP-2 MD5 Authentication |
| RFC 2644 Directed Broadcast Control | RFC 2104 Keyed-Hashing for Message Authentication |
| RFC 2661 L2TP | RFC 2138 RADIUS Authentication |
| RFC 2663 NAT Terminology and Considerations | RFC 2209 RSVP-Message Processing |
| RFC 2684 Multiprotocol Encapsulation over ATM | RFC 2246 Transport Layer Security (TLS) |
| Adaptation Layer 5 | RFC 2716 PPP EAP TLS Authentication Protocol |
| RFC 2694 DNS extensions to Network Address Translators (DNS_ALG) | RFC 2865 RADIUS Authentication |
| RFC 2702 Requirements for Traffic Engineering Over MPLS | RFC 2866 RADIUS Accounting |
| RFC 2747 RSVP Cryptographic Authentication | RFC 3567 Intermediate System (IS) to IS Cryptographic Authentication |
| RFC 2763 Dynamic Name-to-System ID mapping support | VPN |
| RFC 2765 Stateless IP/ICMP Translation Algorithm (SIIT) | RFC 2403 - HMAC-MD5-96 |
| RFC 2766 Network Address Translation - | RFC 2404 - HMAC-SHA1-96 |
| | RFC 2405 - DES-CBC Cipher algorithm |
| | RFC 2547 BGP/MPLS VPNs |
| | RFC 2796 BGP Route Reflection - An Alternative to Full Mesh IBGP |
| | RFC 2842 Capabilities Advertisement with BGP-4 |
| | RFC 2858 Multiprotocol Extensions for BGP-4 |
| | RFC 2918 Route Refresh Capability for BGP-4 |
| | RFC 3107 Carrying Label Information in BGP-4 |

Accessory Product Details

| | |
|--|---|
| Protocol Translation (NAT-PT) | IPsec |
| RFC 2784 Generic Routing Encapsulation (GRE) | RFC 1828 IP Authentication using Keyed MD5 |
| RFC 2787 Definitions of Managed Objects for VRRP | RFC 2401 IP Security Architecture |
| RFC 2961 RSVP Refresh Overhead Reduction Extensions | RFC 2402 IP Authentication Header |
| RFC 2966 Domain-wide Prefix Distribution with Two-Level IS-IS | RFC 2406 IP Encapsulating Security Payload |
| RFC 2973 IS-IS Mesh Groups | RFC 2407 - Domain of interpretation |
| RFC 2993 Architectural Implications of NAT | RFC 2410 - The NULL Encryption Algorithm and its use with IPsec |
| RFC 3022 Traditional IP Network Address Translator (Traditional NAT) | RFC 2411 IP Security Document Roadmap |
| RFC 3027 Protocol Complications with the IP Network Address Translator | RFC 2412 – OAKLEY |
| RFC 3031 Multiprotocol Label Switching Architecture | RFC 2865 - Remote Authentication Dial In User Service (RADIUS) |

HP A-MSR30-20 Multi-Service Router (JF284A)

| | |
|-----------------------------------|---|
| Ports | 4 SIC slots 2 MIM module slots 2 auto-sensing 10/100/1000 ports (IEEE 802.3 Type 10Base-T, IEEE 802.3u Type 100Base-TX, IEEE 802.3ab Type 1000Base-T); Duplex: 10Base-T/100Base-TX: half or full; 1000Base-T: full only |
| Physical characteristics | Dimensions 17.39(d) x 17.4(w) x 1.74(h) in. (44.18 x 44.2 x 4.42 cm) (1U height) Weight 15.21 lb. (6.9 kg) |
| Memory and processor | Processor RISC @ 533 MHz, 256 MB DDR SDRAM, 256 MB compact flash |
| Mounting | Mounts in an EIA standard 19-in. rack |
| Performance | Throughput 300 Kpps (64-byte packets) Routing table size 30,000 entries |
| Environment | Operating temperature 32°F to 104°F (0°C to 40°C) Operating relative humidity 5% to 90%, non-condensing Non-operating/Storage temperature -40°F to 158°F (-40°C to 70°C) Non-operating/Storage relative humidity 5% to 90%, non-condensing |
| Electrical characteristics | Maximum heat dissipation 426 BTU/hr (449.43 kJ/hr) Voltage 100-120 / 200-240 VAC Maximum power rating 125 W Frequency 50 / 60 Hz Notes Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. |
| Safety | UL 60950-1; AS/NZS 60950; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1-03; EN 60950-1/A11; FDA 21 CFR Subchapter J |

Accessory Product Details

| | |
|-------------------|---|
| Emissions | EN 55022 Class A; ICES-003 Class A; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; AS/NZS CISPR22 Class A; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A; EN 55024:1998+ A1:2001 + A2:2003; EN 61000-4-11:2004; EN 61000-4-8:2001 |
| Telecom | FCC part 68 |
| Management | IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager; Telnet; RMON1; FTP; IEEE 802.3 Ethernet MIB |
| Services | <p>3-year, parts only, global next-day advance exchange (UX150E)</p> <p>3-year, 4-hour onsite, 13x5 coverage for hardware (UX151E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UX154E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UX157E)</p> <p>3-year, 24x7 SW phone support, software updates (UX160E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UX152E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UX155E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UX158E)</p> <p>4-year, 24x7 SW phone support, software updates (UX161E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (UX153E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (UX156E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UX159E)</p> <p>5-year, 24x7 SW phone support, software updates (UX162E)</p> <p>3 Yr 6 hr Call-to-Repair Onsite (UX163E)</p> <p>4 Yr 6 hr Call-to-Repair Onsite (UX164E)</p> <p>5 Yr 6 hr Call-to-Repair Onsite (UX165E)</p> |

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Standards and protocols

(applies to all products in series)

BGP

RFC 1163 Border Gateway Protocol (BGP)
 RFC 1267 Border Gateway Protocol 3 (BGP-3)
 RFC 1657 Definitions of Managed Objects for BGPv4
 RFC 1771 BGPv4
 RFC 1772 Application of the BGP
 RFC 1773 Experience with the BGP-4 Protocol
 RFC 1774 BGP-4 Protocol Analysis
 RFC 1965 BGP4 confederations
 RFC 1997 BGP Communities Attribute
 RFC 1998 PPP Gandalf FZA Compression Protocol
 RFC 2385 BGP Session Protection via TCP MD5
 RFC 2439 BGP Route Flap Damping

Device management

RFC 1305 NTPv3
 RFC 1945 Hypertext Transfer Protocol -- HTTP/1.0
 RFC 2271 FrameWork
 RFC 2452 MIB for TCP6
 RFC 2454 MIB for UDP6

General protocols

IEEE 802.1D MAC Bridges
 IEEE 802.1p Priority

RFC 3032 MPLS Label Stack Encoding
 RFC 3036 LDP Specification
 RFC 3046 DHCP Relay Agent Information Option
 RFC 3063 MPLS Loop Prevention Mechanism
 RFC 3065 Support AS confederation
 RFC 3137 OSPF Stub Router Advertisement
 RFC 3209 RSVP-TE Extensions to RSVP for LSP Tunnels
 RFC 3210 Applicability Statement for Extensions to RSVP for LSP-Tunnels
 RFC 3212 Constraint-Based LSP setup using LDP (CR-LDP)
 RFC 3214 LSP Modification Using CR-LDP
 RFC 3215 LDP State Machine
 RFC 3246 Expedited Forwarding PHB
 RFC 3268 Advanced Encryption Standard (AES) Ciphersuites for Transport Layer Security (TLS)
 RFC 3277 IS-IS Transient Blackhole Avoidance
 RFC 3279 Algorithms and Identifiers for the Internet
 X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
 RFC 3280 Internet X.509 Public Key Infrastructure

Accessory Product Details

| | |
|---|--|
| IEEE 802.1Q VLANs | Certificate and Certificate Revocation List (CRL) Profile |
| IEEE 802.1s Multiple Spanning Trees | RFC 3392 Support BGP capabilities advertisement |
| IEEE 802.1w Rapid Reconfiguration of Spanning Tree | RFC 3479 Fault Tolerance for the Label Distribution Protocol (LDP) |
| RFC 768 UDP | RFC 3564 Requirements for Support of Differentiated Services-aware MPLS Traffic Engineering |
| RFC 783 TFTP Protocol (revision 2) | RFC 3602 The AES-CBC Cipher Algorithm and Its Use with IPsec |
| RFC 791 IP | RFC 3706 A Traffic-Based Method of Detecting Dead Internet Key Exchange (IKE) Peers |
| RFC 792 ICMP | RFC 3784 ISIS TE support |
| RFC 793 TCP | RFC 3786 Extending the Number of IS-IS LSP Fragments Beyond the 256 Limit |
| RFC 826 ARP | RFC 3811 Definitions of Textual Conventions (TCs) for Multiprotocol Label Switching (MPLS) Management |
| RFC 854 TELNET | RFC 3812 Multiprotocol Label Switching (MPLS) Traffic Engineering (TE) Management Information Base (MIB) |
| RFC 855 Telnet Option Specification | RFC 3847 Restart signaling for IS-IS |
| RFC 856 TELNET | |
| RFC 858 Telnet Suppress Go Ahead Option | |
| RFC 894 IP over Ethernet | |
| RFC 925 Multi-LAN Address Resolution | |
| RFC 950 Internet Standard Subnetting Procedure | |
| RFC 959 File Transfer Protocol (FTP) | |
| RFC 1006 ISO transport services on top of the TCP: Version 3 | |
| RFC 1027 Proxy ARP | |
| RFC 1034 Domain Concepts and Facilities | |
| RFC 1035 Domain Implementation and Specification | |
| RFC 1042 IP Datagrams | |
| RFC 1058 RIPv1 | |
| RFC 1071 Computing the Internet Checksum | IP multicast |
| RFC 1091 Telnet Terminal-Type Option | RFC 1112 IGMP |
| RFC 1122 Host Requirements | RFC 2236 IGMPv2 |
| RFC 1141 Incremental updating of the Internet checksum | RFC 2283 Multiprotocol Extensions for BGP-4 |
| RFC 1142 OSI IS-IS Intra-domain Routing Protocol | RFC 2362 PIM Sparse Mode |
| RFC 1144 Compressing TCP/IP headers for low-speed serial links | RFC 2934 Protocol Independent Multicast MIB for IPv4 |
| RFC 1195 OSI ISIS for IP and Dual Environments | RFC 3376 IGMPv3 |
| RFC 1256 ICMP Router Discovery Protocol (IRDP) | |
| RFC 1293 Inverse Address Resolution Protocol | IPv6 |
| RFC 1315 Management Information Base for Frame Relay DTEs | RFC 1981 IPv6 Path MTU Discovery |
| RFC 1332 The PPP Internet Protocol Control Protocol (IPCP) | RFC 2080 RIPng for IPv6 |
| RFC 1333 PPP Link Quality Monitoring | RFC 2292 Advanced Sockets API for IPv6 |
| RFC 1334 PPP Authentication Protocols (PAP) | RFC 2373 IPv6 Addressing Architecture |
| RFC 1349 Type of Service | RFC 2460 IPv6 Specification |
| RFC 1350 TFTP Protocol (revision 2) | RFC 2461 IPv6 Neighbor Discovery |
| RFC 1377 The PPP OSI Network Layer Control Protocol (OSINLCP) | RFC 2462 IPv6 Stateless Address Auto-configuration |
| RFC 1381 SNMP MIB Extension for X.25 LAPB | RFC 2464 Transmission of IPv6 over Ethernet Networks |
| RFC 1471 The Definitions of Managed Objects for the Link Control Protocol of the Point-to-Point | RFC 2472 IP Version 6 over PPP |
| | RFC 2473 Generic Packet Tunneling in IPv6 |
| | RFC 2529 Transmission of IPv6 Packets over IPv4 |
| | RFC 2545 Use of MP-BGP-4 for IPv6 |
| | RFC 2553 Basic Socket Interface Extensions for IPv6 |
| | RFC 2740 OSPFv3 for IPv6 |
| | RFC 2893 Transition Mechanisms for IPv6 |

Accessory Product Details

| | |
|--|--|
| Protocol | Hosts |
| RFC 1472 The Definitions of Managed Objects for the Security Protocols of the Point-to-Point Protocol | and Routers |
| RFC 1490 Multiprotocol Interconnect over Frame Relay | RFC 3056 Connection of IPv6 Domains via IPv4 Clouds |
| RFC 1519 CIDR | RFC 3513 IPv6 Addressing Architecture |
| RFC 1534 DHCP/BOOTP Interoperation | RFC 3596 DNS Extension for IPv6 |
| RFC 1542 Clarifications and Extensions for the Bootstrap Protocol | MIBs |
| RFC 1552 The PPP Internetworking Packet Exchange Control Protocol (IPXCP) | RFC 1213 MIB II |
| RFC 1577 Classical IP and ARP over ATM | RFC 1229 Interface MIB Extensions |
| RFC 1613 Cisco Systems X.25 over TCP (XOT) | RFC 1286 Bridge MIB |
| RFC 1624 Incremental Internet Checksum | RFC 1493 Bridge MIB |
| RFC 1631 NAT | RFC 1573 SNMP MIB II |
| RFC 1638 PPP Bridging Control Protocol (BCP) | RFC 1724 RIPv2 MIB |
| RFC 1661 The Point-to-Point Protocol (PPP) | RFC 1757 Remote Network Monitoring MIB |
| RFC 1662 PPP in HDLC-like Framing | RFC 1850 OSPFv2 MIB |
| RFC 1695 Definitions of Managed Objects for ATM Management Version 8.0 using SMIv2 | RFC 2011 SNMPv2 MIB for IP |
| RFC 1701 Generic Routing Encapsulation | RFC 2012 SNMPv2 MIB for TCP |
| RFC 1702 Generic Routing Encapsulation over IPv4 networks | RFC 2013 SNMPv2 MIB for UDP |
| RFC 1721 RIP-2 Analysis | RFC 2233 Interfaces MIB |
| RFC 1722 RIP-2 Applicability | RFC 2454 IPV6-UDP-MIB |
| RFC 1723 RIP v2 | RFC 2465 IPv6 MIB |
| RFC 1795 Data Link Switching: Switch-to-Switch Protocol AIW DLSw RIG: DLSw Closed Pages, DLSw Standard Version 1 | RFC 2466 ICMPv6 MIB |
| RFC 1812 IPv4 Routing | RFC 2618 RADIUS Client MIB |
| RFC 1829 The ESP DES-CBC Transform | RFC 2620 RADIUS Accounting MIB |
| RFC 1877 PPP Internet Protocol Control Protocol | RFC 2674 802.1p and IEEE 802.1Q Bridge MIB |
| Extensions for Name Server Addresses | RFC 2737 Entity MIB (Version 2) |
| RFC 1944 Benchmarking Methodology for Network Interconnect Devices | RFC 2863 The Interfaces Group MIB |
| RFC 1973 PPP in Frame Relay | RFC 2933 IGMP MIB |
| RFC 1974 PPP Stac LZS Compression Protocol | RFC 3813 MPLS LSR MIB |
| RFC 1990 The PPP Multilink Protocol (MP) | Network management |
| RFC 1994 PPP Challenge Handshake Authentication Protocol (CHAP) | IEEE 802.1D (STP) |
| RFC 2091 Trigger RIP | RFC 1155 Structure of Management Information |
| RFC 2131 DHCP | RFC 1157 SNMPv1 |
| RFC 2132 DHCP Options and BOOTP Vendor Extensions | RFC 1905 SNMPv2 Protocol Operations |
| RFC 2166 APPN Implementer's Workshop Closed Pages Document DLSw v2.0 Enhancements | RFC 2272 SNMPv3 Management Protocol |
| RFC 2205 Resource ReSerVation Protocol | RFC 2273 SNMPv3 Applications |
| | RFC 2274 USM for SNMPv3 |
| | RFC 2275 VACM for SNMPv3 |
| | RFC 2575 SNMPv3 View-based Access Control Model (VACM) |
| | RFC 3164 BSD syslog Protocol |
| | OSPF |
| | RFC 1245 OSPF protocol analysis |
| | RFC 1246 Experience with OSPF |
| | RFC 1587 OSPF NSSA |
| | RFC 1765 OSPF Database Overflow |
| | RFC 1850 OSPFv2 Management Information Base (MIB), traps |
| | RFC 2328 OSPFv2 |
| | RFC 2370 OSPF Opaque LSA Option |
| | RFC 3101 OSPF NSSA |
| | QoS/CoS |
| | IEEE 802.1P (CoS) |

Accessory Product Details

(RSVP) -
Version 1 Functional Specification
RFC 2280 Routing Policy Specification
Language
(RPSL)
RFC 2284 EAP over LAN
RFC 2338 VRRP
RFC 2364 PPP Over AAL5
RFC 2374 An Aggregatable Global Unicast
Address Format
RFC 2451 The ESP CBC-Mode Cipher
Algorithms
RFC 2453 RIPv2
RFC 2510 Internet X.509 Public Key
Infrastructure
Certificate Management Protocols
RFC 2511 Internet X.509 Certificate Request
Message Format
RFC 2516 A Method for Transmitting PPP Over
Ethernet (PPPoE)
RFC 2644 Directed Broadcast Control
RFC 2661 L2TP
RFC 2663 NAT Terminology and Considerations
RFC 2684 Multiprotocol Encapsulation over
ATM
Adaptation Layer 5
RFC 2694 DNS extensions to Network Address
Translators (DNS_ALG)
RFC 2702 Requirements for Traffic Engineering
Over MPLS
RFC 2747 RSVP Cryptographic Authentication
RFC 2763 Dynamic Name-to-System ID
mapping
support
RFC 2765 Stateless IP/ICMP Translation
Algorithm
(SIIT)
RFC 2766 Network Address Translation -
Protocol
Translation (NAT-PT)
RFC 2784 Generic Routing Encapsulation
(GRE)
RFC 2787 Definitions of Managed Objects for
VRRP
RFC 2961 RSVP Refresh Overhead Reduction
Extensions
RFC 2966 Domain-wide Prefix Distribution with
Two-Level IS-IS
RFC 2973 IS-IS Mesh Groups
RFC 2993 Architectural Implications of NAT
RFC 3022 Traditional IP Network Address
Translator (Traditional NAT)
RFC 3027 Protocol Complications with the IP
Network Address Translator
RFC 3031 Multiprotocol Label Switching
Architecture

RFC 2474 DS Field in the IPv4 and IPv6
Headers
RFC 2475 DiffServ Architecture
RFC 2597 DiffServ Assured Forwarding (AF)
RFC 2598 DiffServ Expedited Forwarding (EF)
RFC 3168 The Addition of Explicit Congestion
Notification (ECN) to IP

Security

IEEE 802.1X Port Based Network Access
Control
RFC 1321 The MD5 Message-Digest Algorithm
RFC 2082 RIP-2 MD5 Authentication
RFC 2104 Keyed-Hashing for Message
Authentication
RFC 2138 RADIUS Authentication
RFC 2209 RSVP-Message Processing
RFC 2246 Transport Layer Security (TLS)
RFC 2716 PPP EAP TLS Authentication
Protocol
RFC 2865 RADIUS Authentication
RFC 2866 RADIUS Accounting
RFC 3567 Intermediate System (IS) to IS
Cryptographic Authentication

VPN

RFC 2403 - HMAC-MD5-96
RFC 2404 - HMAC-SHA1-96
RFC 2405 - DES-CBC Cipher algorithm
RFC 2547 BGP/MPLS VPNs
RFC 2796 BGP Route Reflection - An
Alternative to
Full Mesh IBGP
RFC 2842 Capabilities Advertisement with BGP-
4
RFC 2858 Multiprotocol Extensions for BGP-4
RFC 2918 Route Refresh Capability for BGP-4
RFC 3107 Carrying Label Information in BGP-4

IPsec

RFC 1828 IP Authentication using Keyed MD5
RFC 2401 IP Security Architecture
RFC 2402 IP Authentication Header
RFC 2406 IP Encapsulating Security Payload
RFC 2407 - Domain of interpretation
RFC 2410 - The NULL Encryption Algorithm and
its
use with IPsec
RFC 2411 IP Security Document Roadmap
RFC 2412 - OAKLEY
RFC 2865 - Remote Authentication Dial In User
Service (RADIUS)

Accessory Product Details

HP A-MSR30-20 PoE Multi-Service Router (JF802A)

| | |
|-----------------------------------|--|
| Ports | 4 SIC slots 2 MIM module slots 2 auto-sensing 10/100/1000 ports (IEEE 802.3 Type 10Base-T, IEEE 802.3u Type 100Base-TX, IEEE 802.3ab Type 1000Base-T); Duplex: 10Base-T/100Base-TX: half or full; 1000Base-T: full only |
| Physical characteristics | Dimensions 17.39(d) x 17.4(w) x 1.74(h) in. (44.18 x 44.2 x 4.42 cm) (1U height) Weight 15.21 lb. (6.9 kg) |
| Memory and processor | Processor RISC @ 533 MHz, 256 MB DDR SDRAM, 256 MB compact flash |
| Mounting | Mounts in an EIA standard 19-in. rack |
| Performance | Throughput 300 Kpps (64-byte packets) Routing table size 30,000 entries |
| Environment | Operating temperature 32°F to 104°F (0°C to 40°C) Operating relative humidity 5% to 90%, non-condensing Non-operating/Storage temperature -40°F to 158°F (-40°C to 70°C) Non-operating/Storage relative humidity 5% to 90%, non-condensing |
| Electrical characteristics | Maximum heat dissipation 426 BTU/hr (449.43 kJ/hr) Voltage 100-120 / 200-240 VAC Maximum power rating 125 W PoE power 150 W Frequency 50 / 60 Hz Notes Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. PoE power is the power supplied by the internal power supply. It is dependent on the type and quantity of power supplies and may be supplemented with the use of an external power supply (EPS). |
| Safety | UL 60950-1; AS/NZS 60950; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1-03; EN 60950-1/A11; FDA 21 CFR Subchapter J |
| Emissions | EN 55022 Class A; ICES-003 Class A; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; AS/NZS CISPR22 Class A; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A; EN 55024:1998+ A1:2001 + A2:2003; EN 61000-4-11:2004; EN 61000-4-8:2001 |
| Telecom | FCC part 68 |
| Management | IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager; Telnet; RMON1; FTP; IEEE 802.3 Ethernet MIB |
| Services | 3-year, parts only, global next-day advance exchange (UX150E) 3-year, 4-hour onsite, 13x5 coverage for hardware (UX151E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UX154E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UX157E) 3-year, 24x7 SW phone support, software updates (UX160E) 4-year, 4-hour onsite, 13x5 coverage for hardware (UX152E) 4-year, 4-hour onsite, 24x7 coverage for hardware (UX155E) 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UX158E) 4-year, 24x7 SW phone support, software updates (UX161E) |

Accessory Product Details

- 5-year, 4-hour onsite, 13x5 coverage for hardware (UX153E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware (UX156E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UX159E)
- 5-year, 24x7 SW phone support, software updates (UX162E)
- 3 Yr 6 hr Call-to-Repair Onsite (UX163E)
- 4 Yr 6 hr Call-to-Repair Onsite (UX164E)
- 5 Yr 6 hr Call-to-Repair Onsite (UX165E)

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Standards and protocols

(applies to all products in series)

BGP

- RFC 1163 Border Gateway Protocol (BGP)
- RFC 1267 Border Gateway Protocol 3 (BGP-3)
- RFC 1657 Definitions of Managed Objects for BGPv4
- RFC 1771 BGPv4
- RFC 1772 Application of the BGP
- RFC 1773 Experience with the BGP-4 Protocol
- RFC 1774 BGP-4 Protocol Analysis
- RFC 1965 BGP4 confederations
- RFC 1997 BGP Communities Attribute
- RFC 1998 PPP Gandalf FZA Compression Protocol
- RFC 2385 BGP Session Protection via TCP MD5
- RFC 2439 BGP Route Flap Damping

Device management

- RFC 1305 NTPv3
- RFC 1945 Hypertext Transfer Protocol -- HTTP/1.0
- RFC 2271 FrameWork
- RFC 2452 MIB for TCP6
- RFC 2454 MIB for UDP6

General protocols

- IEEE 802.1D MAC Bridges
- IEEE 802.1p Priority
- IEEE 802.1Q VLANs
- IEEE 802.1s Multiple Spanning Trees
- IEEE 802.1w Rapid Reconfiguration of Spanning Tree
- RFC 768 UDP
- RFC 783 TFTP Protocol (revision 2)
- RFC 791 IP
- RFC 792 ICMP
- RFC 793 TCP
- RFC 826 ARP
- RFC 854 TELNET
- RFC 855 Telnet Option Specification
- RFC 856 TELNET
- RFC 858 Telnet Suppress Go Ahead Option
- RFC 894 IP over Ethernet
- RFC 925 Multi-LAN Address Resolution
- RFC 950 Internet Standard Subnetting Procedure

- RFC 3032 MPLS Label Stack Encoding
- RFC 3036 LDP Specification
- RFC 3046 DHCP Relay Agent Information Option
- RFC 3063 MPLS Loop Prevention Mechanism
- RFC 3065 Support AS confederation
- RFC 3137 OSPF Stub Router Advertisement
- RFC 3209 RSVP-TE Extensions to RSVP for LSP Tunnels
- RFC 3210 Applicability Statement for Extensions to RSVP for LSP-Tunnels
- RFC 3212 Constraint-Based LSP setup using LDP (CR-LDP)
- RFC 3214 LSP Modification Using CR-LDP
- RFC 3215 LDP State Machine
- RFC 3246 Expedited Forwarding PHB
- RFC 3268 Advanced Encryption Standard (AES) Ciphersuites for Transport Layer Security (TLS)
- RFC 3277 IS-IS Transient Blackhole Avoidance
- RFC 3279 Algorithms and Identifiers for the Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
- RFC 3280 Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
- RFC 3392 Support BGP capabilities advertisement
- RFC 3479 Fault Tolerance for the Label Distribution Protocol (LDP)
- RFC 3564 Requirements for Support of Differentiated Services-aware MPLS Traffic Engineering
- RFC 3602 The AES-CBC Cipher Algorithm and Its Use with IPsec
- RFC 3706 A Traffic-Based Method of Detecting Dead Internet Key Exchange (IKE) Peers
- RFC 3784 ISIS TE support
- RFC 3786 Extending the Number of IS-IS LSP Fragments Beyond the 256 Limit

Accessory Product Details

| | |
|--|--|
| RFC 959 File Transfer Protocol (FTP) | RFC 3811 Definitions of Textual Conventions (TCs) |
| RFC 1006 ISO transport services on top of the TCP: | for Multiprotocol Label Switching (MPLS) Management |
| Version 3 | RFC 3812 Multiprotocol Label Switching (MPLS) Traffic Engineering (TE) Management Information Base (MIB) |
| RFC 1027 Proxy ARP | RFC 3847 Restart signaling for IS-IS |
| RFC 1034 Domain Concepts and Facilities | |
| RFC 1035 Domain Implementation and Specification | |
| RFC 1042 IP Datagrams | |
| RFC 1058 RIPv1 | |
| RFC 1071 Computing the Internet Checksum | IP multicast |
| RFC 1091 Telnet Terminal-Type Option | RFC 1112 IGMP |
| RFC 1122 Host Requirements | RFC 2236 IGMPv2 |
| RFC 1141 Incremental updating of the Internet checksum | RFC 2283 Multiprotocol Extensions for BGP-4 |
| RFC 1142 OSI IS-IS Intra-domain Routing Protocol | RFC 2362 PIM Sparse Mode |
| RFC 1144 Compressing TCP/IP headers for low-speed serial links | RFC 2934 Protocol Independent Multicast MIB for IPv4 |
| RFC 1195 OSI ISIS for IP and Dual Environments | RFC 3376 IGMPv3 |
| RFC 1256 ICMP Router Discovery Protocol (IRDP) | |
| RFC 1293 Inverse Address Resolution Protocol | IPv6 |
| RFC 1315 Management Information Base for Frame Relay DTEs | RFC 1981 IPv6 Path MTU Discovery |
| RFC 1332 The PPP Internet Protocol Control Protocol (IPCP) | RFC 2080 RIPng for IPv6 |
| RFC 1333 PPP Link Quality Monitoring | RFC 2292 Advanced Sockets API for IPv6 |
| RFC 1334 PPP Authentication Protocols (PAP) | RFC 2373 IPv6 Addressing Architecture |
| RFC 1349 Type of Service | RFC 2460 IPv6 Specification |
| RFC 1350 TFTP Protocol (revision 2) | RFC 2461 IPv6 Neighbor Discovery |
| RFC 1377 The PPP OSI Network Layer Control Protocol (OSINLCP) | RFC 2462 IPv6 Stateless Address Auto-configuration |
| RFC 1381 SNMP MIB Extension for X.25 LAPB | RFC 2464 Transmission of IPv6 over Ethernet Networks |
| RFC 1471 The Definitions of Managed Objects for the Link Control Protocol of the Point-to-Point Protocol | RFC 2472 IP Version 6 over PPP |
| RFC 1472 The Definitions of Managed Objects for the Security Protocols of the Point-to-Point Protocol | RFC 2473 Generic Packet Tunneling in IPv6 |
| RFC 1490 Multiprotocol Interconnect over Frame Relay | RFC 2529 Transmission of IPv6 Packets over IPv4 |
| RFC 1519 CIDR | RFC 2545 Use of MP-BGP-4 for IPv6 |
| RFC 1534 DHCP/BOOTP Interoperation | RFC 2553 Basic Socket Interface Extensions for IPv6 |
| RFC 1542 Clarifications and Extensions for the Bootstrap Protocol | RFC 2740 OSPFv3 for IPv6 |
| RFC 1552 The PPP Internetworking Packet Exchange Control Protocol (IPXCP) | RFC 2893 Transition Mechanisms for IPv6 Hosts and Routers |
| RFC 1577 Classical IP and ARP over ATM | RFC 3056 Connection of IPv6 Domains via IPv4 Clouds |
| RFC 1613 Cisco Systems X.25 over TCP (XOT) | RFC 3513 IPv6 Addressing Architecture |
| RFC 1624 Incremental Internet Checksum | RFC 3596 DNS Extension for IPv6 |
| | MIBs |
| | RFC 1213 MIB II |
| | RFC 1229 Interface MIB Extensions |
| | RFC 1286 Bridge MIB |
| | RFC 1493 Bridge MIB |
| | RFC 1573 SNMP MIB II |
| | RFC 1724 RIPv2 MIB |
| | RFC 1757 Remote Network Monitoring MIB |
| | RFC 1850 OSPFv2 MIB |
| | RFC 2011 SNMPv2 MIB for IP |
| | RFC 2012 SNMPv2 MIB for TCP |

Accessory Product Details

| | |
|--|---|
| RFC 1631 NAT | RFC 2013 SNMPv2 MIB for UDP |
| RFC 1638 PPP Bridging Control Protocol (BCP) | RFC 2233 Interfaces MIB |
| RFC 1661 The Point-to-Point Protocol (PPP) | RFC 2454 IPV6-UDP-MIB |
| RFC 1662 PPP in HDLC-like Framing | RFC 2465 IPv6 MIB |
| RFC 1695 Definitions of Managed Objects for ATM | RFC 2466 ICMPv6 MIB |
| Management Version 8.0 using SMIv2 | RFC 2618 RADIUS Client MIB |
| RFC 1701 Generic Routing Encapsulation | RFC 2620 RADIUS Accounting MIB |
| RFC 1702 Generic Routing Encapsulation over IPv4 networks | RFC 2674 802.1p and IEEE 802.1Q Bridge MIB |
| RFC 1721 RIP-2 Analysis | RFC 2737 Entity MIB (Version 2) |
| RFC 1722 RIP-2 Applicability | RFC 2863 The Interfaces Group MIB |
| RFC 1723 RIP v2 | RFC 2933 IGMP MIB |
| RFC 1795 Data Link Switching: Switch-to-Switch Protocol AIW DLSw RIG: DLSw Closed Pages, DLSw Standard Version 1 | RFC 3813 MPLS LSR MIB |
| RFC 1812 IPv4 Routing | Network management |
| RFC 1829 The ESP DES-CBC Transform | IEEE 802.1D (STP) |
| RFC 1877 PPP Internet Protocol Control Protocol | RFC 1155 Structure of Management Information |
| Extensions for Name Server Addresses | RFC 1157 SNMPv1 |
| RFC 1944 Benchmarking Methodology for Network Interconnect Devices | RFC 1905 SNMPv2 Protocol Operations |
| RFC 1973 PPP in Frame Relay | RFC 2272 SNMPv3 Management Protocol |
| RFC 1974 PPP Stac LZS Compression Protocol | RFC 2273 SNMPv3 Applications |
| RFC 1990 The PPP Multilink Protocol (MP) | RFC 2274 USM for SNMPv3 |
| RFC 1994 PPP Challenge Handshake Authentication Protocol (CHAP) | RFC 2275 VACM for SNMPv3 |
| RFC 2091 Trigger RIP | RFC 2575 SNMPv3 View-based Access Control Model (VACM) |
| RFC 2131 DHCP | RFC 3164 BSD syslog Protocol |
| RFC 2132 DHCP Options and BOOTP Vendor Extensions | OSPF |
| RFC 2166 APPN Implementer's Workshop Closed | RFC 1245 OSPF protocol analysis |
| Pages Document DLSw v2.0 Enhancements | RFC 1246 Experience with OSPF |
| RFC 2205 Resource ReSerVation Protocol (RSVP) - Version 1 Functional Specification | RFC 1587 OSPF NSSA |
| RFC 2280 Routing Policy Specification Language (RPSL) | RFC 1765 OSPF Database Overflow |
| RFC 2284 EAP over LAN | RFC 1850 OSPFv2 Management Information Base (MIB), traps |
| RFC 2338 VRRP | RFC 2328 OSPFv2 |
| RFC 2364 PPP Over AAL5 | RFC 2370 OSPF Opaque LSA Option |
| RFC 2374 An Aggregatable Global Unicast Address Format | RFC 3101 OSPF NSSA |
| RFC 2451 The ESP CBC-Mode Cipher Algorithms | QoS/CoS |
| RFC 2453 RIPv2 | IEEE 802.1P (CoS) |
| RFC 2510 Internet X.509 Public Key Infrastructure Certificate Management Protocols | RFC 2474 DS Field in the IPv4 and IPv6 Headers |
| RFC 2511 Internet X.509 Certificate Request Message Format | RFC 2475 DiffServ Architecture |
| | RFC 2597 DiffServ Assured Forwarding (AF) |
| | RFC 2598 DiffServ Expedited Forwarding (EF) |
| | RFC 3168 The Addition of Explicit Congestion Notification (ECN) to IP |
| | Security |
| | IEEE 802.1X Port Based Network Access Control |
| | RFC 1321 The MD5 Message-Digest Algorithm |
| | RFC 2082 RIP-2 MD5 Authentication |
| | RFC 2104 Keyed-Hashing for Message Authentication |
| | RFC 2138 RADIUS Authentication |
| | RFC 2209 RSVP-Message Processing |
| | RFC 2246 Transport Layer Security (TLS) |

Accessory Product Details

| | |
|--|--|
| RFC 2516 A Method for Transmitting PPP Over Ethernet (PPPoE) | RFC 2716 PPP EAP TLS Authentication Protocol |
| RFC 2644 Directed Broadcast Control | RFC 2865 RADIUS Authentication |
| RFC 2661 L2TP | RFC 2866 RADIUS Accounting |
| RFC 2663 NAT Terminology and Considerations | RFC 3567 Intermediate System (IS) to IS Cryptographic Authentication |
| RFC 2684 Multiprotocol Encapsulation over ATM | |
| Adaptation Layer 5 | VPN |
| RFC 2694 DNS extensions to Network Address Translators (DNS_ALG) | RFC 2403 - HMAC-MD5-96 |
| RFC 2702 Requirements for Traffic Engineering Over MPLS | RFC 2404 - HMAC-SHA1-96 |
| RFC 2747 RSVP Cryptographic Authentication | RFC 2405 - DES-CBC Cipher algorithm |
| RFC 2763 Dynamic Name-to-System ID mapping support | RFC 2547 BGP/MPLS VPNs |
| RFC 2765 Stateless IP/ICMP Translation Algorithm (SIIT) | RFC 2796 BGP Route Reflection - An Alternative to Full Mesh IBGP |
| RFC 2766 Network Address Translation - Protocol | RFC 2842 Capabilities Advertisement with BGP-4 |
| Translation (NAT-PT) | RFC 2858 Multiprotocol Extensions for BGP-4 |
| RFC 2784 Generic Routing Encapsulation (GRE) | RFC 2918 Route Refresh Capability for BGP-4 |
| RFC 2787 Definitions of Managed Objects for VRRP | RFC 3107 Carrying Label Information in BGP-4 |
| RFC 2961 RSVP Refresh Overhead Reduction Extensions | |
| RFC 2966 Domain-wide Prefix Distribution with Two-Level IS-IS | IPsec |
| RFC 2973 IS-IS Mesh Groups | RFC 1828 IP Authentication using Keyed MD5 |
| RFC 2993 Architectural Implications of NAT | RFC 2401 IP Security Architecture |
| RFC 3022 Traditional IP Network Address Translator (Traditional NAT) | RFC 2402 IP Authentication Header |
| RFC 3027 Protocol Complications with the IP Network Address Translator | RFC 2406 IP Encapsulating Security Payload |
| RFC 3031 Multiprotocol Label Switching Architecture | RFC 2407 - Domain of interpretation |
| | RFC 2410 - The NULL Encryption Algorithm and its use with IPsec |
| | RFC 2411 IP Security Document Roadmap |
| | RFC 2412 - OAKLEY |
| | RFC 2865 - Remote Authentication Dial In User Service (RADIUS) |

HP A-MSR30-40 Multi-Service Router (JF229A)

| | |
|---------------------------------|---|
| Ports | 4 SIC slots |
| | 4 MIM module slots |
| | 2 1000Base-T ports (IEEE 802.3ab Type 1000Base-T) |
| | 2 fixed Gigabit Ethernet SFP ports |
| Physical characteristics | Dimensions 16.63(d) x 17.4(w) x 3.47(h) in. (42.23 x 44.2 x 8.82 cm) (2U height) |
| | Weight 26.23 lb. (11.9 kg) |
| Memory and processor | Processor RISC @ 533 MHz, 256 MB DDR SDRAM, 256 MB compact flash |
| Mounting | Mounts in an EIA standard 19-in. rack |
| Performance | Throughput 360 Kpps (64-byte packets) |
| | Routing table size 30,000 entries |
| Environment | Operating temperature 32°F to 104°F (0°C to 40°C) |
| | Operating relative humidity 5% to 90%, non-condensing |

Accessory Product Details

| | | |
|---|---|---|
| | Non-operating/Storage temperature -40°F to 158°F (-40°C to 70°C) | |
| | Non-operating/Storage relative humidity 5% to 90%, non-condensing | |
| Electrical characteristics | Maximum heat dissipation | 717 BTU/hr (756.44 kJ/hr) |
| | Voltage | 100-120 / 200-240 VAC |
| | Maximum power rating | 210 W |
| | Frequency | 50 / 60 Hz |
| | Notes | Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. |
| Safety | UL 60950-1; AS/NZS 60950; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1-03; EN 60950-1/A11; FDA 21 CFR Subchapter J | |
| Emissions | EN 55022 Class A; ICES-003 Class A; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; AS/NZS CISPR22 Class A; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A; EN 55024:1998+ A1:2001 + A2:2003; EN 61000-4-11:2004; EN 61000-4-8:2001 | |
| Telecom Management | FCC part 68 IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager; Telnet; RMON1; FTP; IEEE 802.3 Ethernet MIB | |
| Services | <p>3-year, parts only, global next-day advance exchange (UX150E)</p> <p>3-year, 4-hour onsite, 13x5 coverage for hardware (UX151E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UX154E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UX157E)</p> <p>3-year, 24x7 SW phone support, software updates (UX160E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UX152E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UX155E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UX158E)</p> <p>4-year, 24x7 SW phone support, software updates (UX161E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (UX153E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (UX156E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UX159E)</p> <p>5-year, 24x7 SW phone support, software updates (UX162E)</p> <p>3 Yr 6 hr Call-to-Repair Onsite (UX163E)</p> <p>4 Yr 6 hr Call-to-Repair Onsite (UX164E)</p> <p>5 Yr 6 hr Call-to-Repair Onsite (UX165E)</p> | |
| | Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office. | |
| Standards and protocols (applies to all products in series) | BGP | <p>RFC 3032 MPLS Label Stack Encoding</p> <p>RFC 3036 LDP Specification</p> <p>RFC 3046 DHCP Relay Agent Information Option</p> <p>RFC 3063 MPLS Loop Prevention Mechanism</p> <p>RFC 3065 Support AS confederation</p> <p>RFC 3137 OSPF Stub Router Advertisement</p> <p>RFC 3209 RSVP-TE Extensions to RSVP for LSP Tunnels</p> |
| | RFC 1163 Border Gateway Protocol (BGP) | |
| | RFC 1267 Border Gateway Protocol 3 (BGP-3) | |
| | RFC 1657 Definitions of Managed Objects for BGPv4 | |
| | RFC 1771 BGPv4 | |
| | RFC 1772 Application of the BGP | |
| | RFC 1773 Experience with the BGP-4 Protocol | |
| | RFC 1774 BGP-4 Protocol Analysis | |
| | RFC 1965 BGP4 confederations | |

Accessory Product Details

RFC 1997 BGP Communities Attribute
RFC 1998 PPP Gandalf FZA Compression Protocol
RFC 2385 BGP Session Protection via TCP MD5
RFC 2439 BGP Route Flap Damping

Device management

RFC 1305 NTPv3
RFC 1945 Hypertext Transfer Protocol -- HTTP/1.0
RFC 2271 FrameWork
RFC 2452 MIB for TCP6
RFC 2454 MIB for UDP6

General protocols

IEEE 802.1D MAC Bridges
IEEE 802.1p Priority
IEEE 802.1Q VLANs
IEEE 802.1s Multiple Spanning Trees
IEEE 802.1w Rapid Reconfiguration of Spanning Tree
RFC 768 UDP
RFC 783 TFTP Protocol (revision 2)
RFC 791 IP
RFC 792 ICMP
RFC 793 TCP
RFC 826 ARP
RFC 854 TELNET
RFC 855 Telnet Option Specification
RFC 856 TELNET
RFC 858 Telnet Suppress Go Ahead Option
RFC 894 IP over Ethernet
RFC 925 Multi-LAN Address Resolution
RFC 950 Internet Standard Subnetting Procedure
RFC 959 File Transfer Protocol (FTP)
RFC 1006 ISO transport services on top of the TCP:
Version 3
RFC 1027 Proxy ARP
RFC 1034 Domain Concepts and Facilities
RFC 1035 Domain Implementation and Specification
RFC 1042 IP Datagrams
RFC 1058 RIPv1
RFC 1071 Computing the Internet Checksum
RFC 1091 Telnet Terminal-Type Option
RFC 1122 Host Requirements
RFC 1141 Incremental updating of the Internet checksum
RFC 1142 OSI IS-IS Intra-domain Routing Protocol
RFC 1144 Compressing TCP/IP headers for low-speed serial links
RFC 1195 OSI ISIS for IP and Dual Environments
RFC 1256 ICMP Router Discovery Protocol

RFC 3210 Applicability Statement for Extensions to
RSVP for LSP-Tunnels
RFC 3212 Constraint-Based LSP setup using LDP
(CR-LDP)
RFC 3214 LSP Modification Using CR-LDP
RFC 3215 LDP State Machine
RFC 3246 Expedited Forwarding PHB
RFC 3268 Advanced Encryption Standard (AES) Ciphersuites for Transport Layer Security (TLS)
RFC 3277 IS-IS Transient Blackhole Avoidance
RFC 3279 Algorithms and Identifiers for the Internet
X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
RFC 3280 Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
RFC 3392 Support BGP capabilities advertisement
RFC 3479 Fault Tolerance for the Label Distribution Protocol (LDP)
RFC 3564 Requirements for Support of Differentiated Services-aware MPLS Traffic Engineering
RFC 3602 The AES-CBC Cipher Algorithm and Its Use with IPsec
RFC 3706 A Traffic-Based Method of Detecting Dead Internet Key Exchange (IKE) Peers
RFC 3784 ISIS TE support
RFC 3786 Extending the Number of IS-IS LSP Fragments Beyond the 256 Limit
RFC 3811 Definitions of Textual Conventions (TCs) for Multiprotocol Label Switching (MPLS) Management
RFC 3812 Multiprotocol Label Switching (MPLS) Traffic Engineering (TE) Management Information Base (MIB)
RFC 3847 Restart signaling for IS-IS

IP multicast

RFC 1112 IGMP
RFC 2236 IGMPv2
RFC 2283 Multiprotocol Extensions for BGP-4
RFC 2362 PIM Sparse Mode
RFC 2934 Protocol Independent Multicast MIB for IPv4
RFC 3376 IGMPv3

IPv6

RFC 1981 IPv6 Path MTU Discovery

Accessory Product Details

| | |
|--|---|
| (IRDP) | RFC 2080 RIPng for IPv6 |
| RFC 1293 Inverse Address Resolution Protocol | RFC 2292 Advanced Sockets API for IPv6 |
| RFC 1315 Management Information Base for Frame | RFC 2373 IPv6 Addressing Architecture |
| Relay DTEs | RFC 2460 IPv6 Specification |
| RFC 1332 The PPP Internet Protocol Control Protocol | RFC 2461 IPv6 Neighbor Discovery |
| (IPCP) | RFC 2462 IPv6 Stateless Address Auto-configuration |
| RFC 1333 PPP Link Quality Monitoring | RFC 2464 Transmission of IPv6 over Ethernet Networks |
| RFC 1334 PPP Authentication Protocols (PAP) | RFC 2472 IP Version 6 over PPP |
| RFC 1349 Type of Service | RFC 2473 Generic Packet Tunneling in IPv6 |
| RFC 1350 TFTP Protocol (revision 2) | RFC 2529 Transmission of IPv6 Packets over IPv4 |
| RFC 1377 The PPP OSI Network Layer Control Protocol (OSINLCP) | RFC 2545 Use of MP-BGP-4 for IPv6 |
| RFC 1381 SNMP MIB Extension for X.25 LAPB | RFC 2553 Basic Socket Interface Extensions for IPv6 |
| RFC 1471 The Definitions of Managed Objects for the Link Control Protocol of the Point-to-Point Protocol | RFC 2740 OSPFv3 for IPv6 |
| RFC 1472 The Definitions of Managed Objects for the Security Protocols of the Point-to-Point Protocol | RFC 2893 Transition Mechanisms for IPv6 Hosts and Routers |
| RFC 1490 Multiprotocol Interconnect over Frame Relay | RFC 3056 Connection of IPv6 Domains via IPv4 Clouds |
| RFC 1519 CIDR | RFC 3513 IPv6 Addressing Architecture |
| RFC 1534 DHCP/BOOTP Interoperation | RFC 3596 DNS Extension for IPv6 |
| RFC 1542 Clarifications and Extensions for the Bootstrap Protocol | |
| RFC 1552 The PPP Internetworking Packet Exchange Control Protocol (IPXCP) | MIBs |
| RFC 1577 Classical IP and ARP over ATM | RFC 1213 MIB II |
| RFC 1613 Cisco Systems X.25 over TCP (XOT) | RFC 1229 Interface MIB Extensions |
| RFC 1624 Incremental Internet Checksum | RFC 1286 Bridge MIB |
| RFC 1631 NAT | RFC 1493 Bridge MIB |
| RFC 1638 PPP Bridging Control Protocol (BCP) | RFC 1573 SNMP MIB II |
| RFC 1661 The Point-to-Point Protocol (PPP) | RFC 1724 RIPv2 MIB |
| RFC 1662 PPP in HDLC-like Framing | RFC 1757 Remote Network Monitoring MIB |
| RFC 1695 Definitions of Managed Objects for ATM Management Version 8.0 using SMIv2 | RFC 1850 OSPFv2 MIB |
| RFC 1701 Generic Routing Encapsulation | RFC 2011 SNMPv2 MIB for IP |
| RFC 1702 Generic Routing Encapsulation over IPv4 networks | RFC 2012 SNMPv2 MIB for TCP |
| RFC 1721 RIP-2 Analysis | RFC 2013 SNMPv2 MIB for UDP |
| RFC 1722 RIP-2 Applicability | RFC 2233 Interfaces MIB |
| RFC 1723 RIP v2 | RFC 2454 IPV6-UDP-MIB |
| RFC 1795 Data Link Switching: Switch-to-Switch Protocol AIW DLSw RIG: DLSw Closed Pages, DLSw Standard Version 1 | RFC 2465 IPv6 MIB |
| RFC 1812 IPv4 Routing | RFC 2466 ICMPv6 MIB |
| RFC 1829 The ESP DES-CBC Transform | RFC 2618 RADIUS Client MIB |
| RFC 1877 PPP Internet Protocol Control Protocol | RFC 2620 RADIUS Accounting MIB |
| | RFC 2674 802.1p and IEEE 802.1Q Bridge MIB |
| | RFC 2737 Entity MIB (Version 2) |
| | RFC 2863 The Interfaces Group MIB |
| | RFC 2933 IGMP MIB |
| | RFC 3813 MPLS LSR MIB |
| | Network management |
| | IEEE 802.1D (STP) |
| | RFC 1155 Structure of Management Information |
| | RFC 1157 SNMPv1 |
| | RFC 1905 SNMPv2 Protocol Operations |
| | RFC 2272 SNMPv3 Management Protocol |
| | RFC 2273 SNMPv3 Applications |
| | RFC 2274 USM for SNMPv3 |
| | RFC 2275 VACM for SNMPv3 |

Accessory Product Details

| | |
|--|---|
| Extensions for Name Server Addresses | RFC 2575 SNMPv3 View-based Access Control Model (VACM) |
| RFC 1944 Benchmarking Methodology for Network Interconnect Devices | RFC 3164 BSD syslog Protocol |
| RFC 1973 PPP in Frame Relay | OSPF |
| RFC 1974 PPP Stac LZS Compression Protocol | RFC 1245 OSPF protocol analysis |
| RFC 1990 The PPP Multilink Protocol (MP) | RFC 1246 Experience with OSPF |
| RFC 1994 PPP Challenge Handshake Authentication Protocol (CHAP) | RFC 1587 OSPF NSSA |
| RFC 2091 Trigger RIP | RFC 1765 OSPF Database Overflow |
| RFC 2131 DHCP | RFC 1850 OSPFv2 Management Information Base (MIB), traps |
| RFC 2132 DHCP Options and BOOTP Vendor Extensions | RFC 2328 OSPFv2 |
| RFC 2166 APPN Implementer's Workshop Closed | RFC 2370 OSPF Opaque LSA Option |
| Pages Document DLSw v2.0 Enhancements | RFC 3101 OSPF NSSA |
| RFC 2205 Resource ReSerVation Protocol (RSVP) - Version 1 Functional Specification | QoS/CoS |
| RFC 2280 Routing Policy Specification Language (RPSL) | IEEE 802.1P (CoS) |
| RFC 2284 EAP over LAN | RFC 2474 DS Field in the IPv4 and IPv6 Headers |
| RFC 2338 VRRP | RFC 2475 DiffServ Architecture |
| RFC 2364 PPP Over AAL5 | RFC 2597 DiffServ Assured Forwarding (AF) |
| RFC 2374 An Aggregatable Global Unicast Address Format | RFC 2598 DiffServ Expedited Forwarding (EF) |
| RFC 2451 The ESP CBC-Mode Cipher Algorithms | RFC 3168 The Addition of Explicit Congestion Notification (ECN) to IP |
| RFC 2453 IPv2 | Security |
| RFC 2510 Internet X.509 Public Key Infrastructure | IEEE 802.1X Port Based Network Access Control |
| Certificate Management Protocols | RFC 1321 The MD5 Message-Digest Algorithm |
| RFC 2511 Internet X.509 Certificate Request Message Format | RFC 2082 RIP-2 MD5 Authentication |
| RFC 2516 A Method for Transmitting PPP Over Ethernet (PPPoE) | RFC 2104 Keyed-Hashing for Message Authentication |
| RFC 2644 Directed Broadcast Control | RFC 2138 RADIUS Authentication |
| RFC 2661 L2TP | RFC 2209 RSVP-Message Processing |
| RFC 2663 NAT Terminology and Considerations | RFC 2246 Transport Layer Security (TLS) |
| RFC 2684 Multiprotocol Encapsulation over ATM | RFC 2716 PPP EAP TLS Authentication Protocol |
| Adaptation Layer 5 | RFC 2865 RADIUS Authentication |
| RFC 2694 DNS extensions to Network Address Translators (DNS_ALG) | RFC 2866 RADIUS Accounting |
| RFC 2702 Requirements for Traffic Engineering Over MPLS | RFC 3567 Intermediate System (IS) to IS Cryptographic Authentication |
| RFC 2747 RSVP Cryptographic Authentication | VPN |
| RFC 2763 Dynamic Name-to-System ID mapping support | RFC 2403 - HMAC-MD5-96 |
| RFC 2765 Stateless IP/ICMP Translation Algorithm (SIIT) | RFC 2404 - HMAC-SHA1-96 |
| RFC 2766 Network Address Translation - Protocol Translation (NAT-PT) | RFC 2405 - DES-CBC Cipher algorithm |
| | RFC 2547 BGP/MPLS VPNs |
| | RFC 2796 BGP Route Reflection - An Alternative to Full Mesh IBGP |
| | RFC 2842 Capabilities Advertisement with BGP-4 |
| | RFC 2858 Multiprotocol Extensions for BGP-4 |
| | RFC 2918 Route Refresh Capability for BGP-4 |
| | RFC 3107 Carrying Label Information in BGP-4 |
| | IPsec |

Accessory Product Details

| | |
|--|---|
| RFC 2784 Generic Routing Encapsulation (GRE) | RFC 1828 IP Authentication using Keyed MD5 |
| RFC 2787 Definitions of Managed Objects for VRRP | RFC 2401 IP Security Architecture |
| RFC 2961 RSVP Refresh Overhead Reduction Extensions | RFC 2402 IP Authentication Header |
| RFC 2966 Domain-wide Prefix Distribution with Two-Level IS-IS | RFC 2406 IP Encapsulating Security Payload |
| RFC 2973 IS-IS Mesh Groups | RFC 2407 - Domain of interpretation |
| RFC 2993 Architectural Implications of NAT | RFC 2410 - The NULL Encryption Algorithm and its use with IPsec |
| RFC 3022 Traditional IP Network Address Translator (Traditional NAT) | RFC 2411 IP Security Document Roadmap |
| RFC 3027 Protocol Complications with the IP Network Address Translator | RFC 2412 – OAKLEY |
| RFC 3031 Multiprotocol Label Switching Architecture | RFC 2865 - Remote Authentication Dial In User Service (RADIUS) |

HP A-MSR30-40 PoE Multi-Service Router (JF803A)

| | |
|-----------------------------------|---|
| Ports | 4 SIC slots |
| | 4 MIM module slots |
| | 2 1000Base-T ports (IEEE 802.3ab Type 1000Base-T) |
| | 2 fixed Gigabit Ethernet SFP ports |
| Physical characteristics | Dimensions 16.63(d) x 17.4(w) x 3.47(h) in. (42.23 x 44.2 x 8.82 cm) (2U height) |
| | Weight 26.23 lb. (11.9 kg) |
| Memory and processor | Processor RISC @ 533 MHz, 256 MB DDR SDRAM, 256 MB compact flash |
| Mounting | Mounts in an EIA standard 19-in. rack |
| Performance | Throughput 360 Kpps (64-byte packets) |
| | Routing table size 30,000 entries |
| | Operating temperature 32°F to 104°F (0°C to 40°C) |
| Environment | Operating relative humidity 5% to 90%, non-condensing |
| | Non-operating/Storage temperature -40°F to 158°F (-40°C to 70°C) |
| | Non-operating/Storage relative humidity 5% to 90%, non-condensing |
| | Maximum heat dissipation 717 BTU/hr (756.44 kJ/hr) |
| Electrical characteristics | Voltage 100-120 / 200-240 VAC |
| | Maximum power rating 210 W |
| | PoE power 375 W |
| | Frequency 50 / 60 Hz |
| | Notes Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. PoE power is the power supplied by the internal power supply. It is dependent on the type and quantity of power supplies and may be supplemented with the use of an external power supply (EPS). |
| | Safety UL 60950-1; AS/NZS 60950; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1-03; FDA 21 CFR Subchapter J |

Accessory Product Details

| | |
|-------------------|---|
| Emissions | EN 55022 Class A; ICES-003 Class A; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; AS/NZS CISPR22 Class A; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A; EN 55024:1998+ A1:2001 + A2:2003; EN 61000-4-11:2004; EN 61000-4-8:2001 |
| Telecom | FCC part 68 |
| Management | IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager; Telnet; RMON1; FTP; IEEE 802.3 Ethernet MIB |
| Services | <p>3-year, parts only, global next-day advance exchange (UX150E)</p> <p>3-year, 4-hour onsite, 13x5 coverage for hardware (UX151E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UX154E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UX157E)</p> <p>3-year, 24x7 SW phone support, software updates (UX160E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UX152E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UX155E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UX158E)</p> <p>4-year, 24x7 SW phone support, software updates (UX161E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (UX153E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (UX156E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UX159E)</p> <p>5-year, 24x7 SW phone support, software updates (UX162E)</p> <p>3 Yr 6 hr Call-to-Repair Onsite (UX163E)</p> <p>4 Yr 6 hr Call-to-Repair Onsite (UX164E)</p> <p>5 Yr 6 hr Call-to-Repair Onsite (UX165E)</p> |

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Standards and protocols

(applies to all products in series)

BGP

RFC 1163 Border Gateway Protocol (BGP)

RFC 1267 Border Gateway Protocol 3 (BGP-3)

RFC 1657 Definitions of Managed Objects for BGPv4

RFC 1771 BGPv4

RFC 1772 Application of the BGP

RFC 1773 Experience with the BGP-4 Protocol

RFC 1774 BGP-4 Protocol Analysis

RFC 1965 BGP4 confederations

RFC 1997 BGP Communities Attribute

RFC 1998 PPP Gandalf FZA Compression Protocol

RFC 2385 BGP Session Protection via TCP MD5

RFC 2439 BGP Route Flap Damping

Device management

RFC 1305 NTPv3

RFC 1945 Hypertext Transfer Protocol -- HTTP/1.0

RFC 2271 FrameWork

RFC 2452 MIB for TCP6

RFC 2454 MIB for UDP6

General protocols

IEEE 802.1D MAC Bridges

IEEE 802.1p Priority

RFC 3032 MPLS Label Stack Encoding

RFC 3036 LDP Specification

RFC 3046 DHCP Relay Agent Information Option

RFC 3063 MPLS Loop Prevention Mechanism

RFC 3065 Support AS confederation

RFC 3137 OSPF Stub Router Advertisement

RFC 3209 RSVP-TE Extensions to RSVP for LSP Tunnels

RFC 3210 Applicability Statement for Extensions to RSVP for LSP-Tunnels

RFC 3212 Constraint-Based LSP setup using LDP (CR-LDP)

RFC 3214 LSP Modification Using CR-LDP

RFC 3215 LDP State Machine

RFC 3246 Expedited Forwarding PHB

RFC 3268 Advanced Encryption Standard (AES) Ciphersuites for Transport Layer Security (TLS)

RFC 3277 IS-IS Transient Blackhole Avoidance

RFC 3279 Algorithms and Identifiers for the Internet

X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile

RFC 3280 Internet X.509 Public Key Infrastructure

Accessory Product Details

| | |
|---|--|
| IEEE 802.1Q VLANs | Certificate and Certificate Revocation List (CRL) Profile |
| IEEE 802.1s Multiple Spanning Trees | RFC 3392 Support BGP capabilities advertisement |
| IEEE 802.1w Rapid Reconfiguration of Spanning Tree | RFC 3479 Fault Tolerance for the Label Distribution Protocol (LDP) |
| RFC 768 UDP | RFC 3564 Requirements for Support of Differentiated Services-aware MPLS Traffic Engineering |
| RFC 783 TFTP Protocol (revision 2) | RFC 3602 The AES-CBC Cipher Algorithm and Its Use with IPsec |
| RFC 791 IP | RFC 3706 A Traffic-Based Method of Detecting Dead Internet Key Exchange (IKE) Peers |
| RFC 792 ICMP | RFC 3784 ISIS TE support |
| RFC 793 TCP | RFC 3786 Extending the Number of IS-IS LSP Fragments Beyond the 256 Limit |
| RFC 826 ARP | RFC 3811 Definitions of Textual Conventions (TCs) for Multiprotocol Label Switching (MPLS) Management |
| RFC 854 TELNET | RFC 3812 Multiprotocol Label Switching (MPLS) Traffic Engineering (TE) Management Information Base (MIB) |
| RFC 855 Telnet Option Specification | RFC 3847 Restart signaling for IS-IS |
| RFC 856 TELNET | |
| RFC 858 Telnet Suppress Go Ahead Option | |
| RFC 894 IP over Ethernet | |
| RFC 925 Multi-LAN Address Resolution | |
| RFC 950 Internet Standard Subnetting Procedure | |
| RFC 959 File Transfer Protocol (FTP) | |
| RFC 1006 ISO transport services on top of the TCP: Version 3 | |
| RFC 1027 Proxy ARP | |
| RFC 1034 Domain Concepts and Facilities | |
| RFC 1035 Domain Implementation and Specification | |
| RFC 1042 IP Datagrams | |
| RFC 1058 RIPv1 | |
| RFC 1071 Computing the Internet Checksum | IP multicast |
| RFC 1091 Telnet Terminal-Type Option | RFC 1112 IGMP |
| RFC 1122 Host Requirements | RFC 2236 IGMPv2 |
| RFC 1141 Incremental updating of the Internet checksum | RFC 2283 Multiprotocol Extensions for BGP-4 |
| RFC 1142 OSI IS-IS Intra-domain Routing Protocol | RFC 2362 PIM Sparse Mode |
| RFC 1144 Compressing TCP/IP headers for low-speed serial links | RFC 2934 Protocol Independent Multicast MIB for IPv4 |
| RFC 1195 OSI ISIS for IP and Dual Environments | RFC 3376 IGMPv3 |
| RFC 1256 ICMP Router Discovery Protocol (IRDP) | |
| RFC 1293 Inverse Address Resolution Protocol | IPv6 |
| RFC 1315 Management Information Base for Frame Relay DTEs | RFC 1981 IPv6 Path MTU Discovery |
| RFC 1332 The PPP Internet Protocol Control Protocol (IPCP) | RFC 2080 RIPng for IPv6 |
| RFC 1333 PPP Link Quality Monitoring | RFC 2292 Advanced Sockets API for IPv6 |
| RFC 1334 PPP Authentication Protocols (PAP) | RFC 2373 IPv6 Addressing Architecture |
| RFC 1349 Type of Service | RFC 2460 IPv6 Specification |
| RFC 1350 TFTP Protocol (revision 2) | RFC 2461 IPv6 Neighbor Discovery |
| RFC 1377 The PPP OSI Network Layer Control Protocol (OSINLCP) | RFC 2462 IPv6 Stateless Address Auto-configuration |
| RFC 1381 SNMP MIB Extension for X.25 LAPB | RFC 2464 Transmission of IPv6 over Ethernet Networks |
| RFC 1471 The Definitions of Managed Objects for the Link Control Protocol of the Point-to-Point | RFC 2472 IP Version 6 over PPP |
| | RFC 2473 Generic Packet Tunneling in IPv6 |
| | RFC 2529 Transmission of IPv6 Packets over IPv4 |
| | RFC 2545 Use of MP-BGP-4 for IPv6 |
| | RFC 2553 Basic Socket Interface Extensions for IPv6 |
| | RFC 2740 OSPFv3 for IPv6 |
| | RFC 2893 Transition Mechanisms for IPv6 |

Accessory Product Details

| | |
|--|--|
| Protocol | Hosts |
| RFC 1472 The Definitions of Managed Objects for the Security Protocols of the Point-to-Point Protocol | and Routers |
| RFC 1490 Multiprotocol Interconnect over Frame Relay | RFC 3056 Connection of IPv6 Domains via IPv4 Clouds |
| RFC 1519 CIDR | RFC 3513 IPv6 Addressing Architecture |
| RFC 1534 DHCP/BOOTP Interoperation | RFC 3596 DNS Extension for IPv6 |
| RFC 1542 Clarifications and Extensions for the Bootstrap Protocol | MIBs |
| RFC 1552 The PPP Internetworking Packet Exchange Control Protocol (IPXCP) | RFC 1213 MIB II |
| RFC 1577 Classical IP and ARP over ATM | RFC 1229 Interface MIB Extensions |
| RFC 1613 Cisco Systems X.25 over TCP (XOT) | RFC 1286 Bridge MIB |
| RFC 1624 Incremental Internet Checksum | RFC 1493 Bridge MIB |
| RFC 1631 NAT | RFC 1573 SNMP MIB II |
| RFC 1638 PPP Bridging Control Protocol (BCP) | RFC 1724 RIPv2 MIB |
| RFC 1661 The Point-to-Point Protocol (PPP) | RFC 1757 Remote Network Monitoring MIB |
| RFC 1662 PPP in HDLC-like Framing | RFC 1850 OSPFv2 MIB |
| RFC 1695 Definitions of Managed Objects for ATM Management Version 8.0 using SMIv2 | RFC 2011 SNMPv2 MIB for IP |
| RFC 1701 Generic Routing Encapsulation | RFC 2012 SNMPv2 MIB for TCP |
| RFC 1702 Generic Routing Encapsulation over IPv4 networks | RFC 2013 SNMPv2 MIB for UDP |
| RFC 1721 RIP-2 Analysis | RFC 2233 Interfaces MIB |
| RFC 1722 RIP-2 Applicability | RFC 2454 IPV6-UDP-MIB |
| RFC 1723 RIP v2 | RFC 2465 IPv6 MIB |
| RFC 1795 Data Link Switching: Switch-to-Switch Protocol AIW DLSw RIG: DLSw Closed Pages, DLSw Standard Version 1 | RFC 2466 ICMPv6 MIB |
| RFC 1812 IPv4 Routing | RFC 2618 RADIUS Client MIB |
| RFC 1829 The ESP DES-CBC Transform | RFC 2620 RADIUS Accounting MIB |
| RFC 1877 PPP Internet Protocol Control Protocol Extensions for Name Server Addresses | RFC 2674 802.1p and IEEE 802.1Q Bridge MIB |
| RFC 1944 Benchmarking Methodology for Network Interconnect Devices | RFC 2737 Entity MIB (Version 2) |
| RFC 1973 PPP in Frame Relay | RFC 2863 The Interfaces Group MIB |
| RFC 1974 PPP Stac LZS Compression Protocol | RFC 2933 IGMP MIB |
| RFC 1990 The PPP Multilink Protocol (MP) | RFC 3813 MPLS LSR MIB |
| RFC 1994 PPP Challenge Handshake Authentication Protocol (CHAP) | Network management |
| RFC 2091 Trigger RIP | IEEE 802.1D (STP) |
| RFC 2131 DHCP | RFC 1155 Structure of Management Information |
| RFC 2132 DHCP Options and BOOTP Vendor Extensions | RFC 1157 SNMPv1 |
| RFC 2166 APPN Implementer's Workshop Closed Pages Document DLSw v2.0 Enhancements | RFC 1905 SNMPv2 Protocol Operations |
| RFC 2205 Resource ReSerVation Protocol | RFC 2272 SNMPv3 Management Protocol |
| | RFC 2273 SNMPv3 Applications |
| | RFC 2274 USM for SNMPv3 |
| | RFC 2275 VACM for SNMPv3 |
| | RFC 2575 SNMPv3 View-based Access Control Model (VACM) |
| | RFC 3164 BSD syslog Protocol |
| | OSPF |
| | RFC 1245 OSPF protocol analysis |
| | RFC 1246 Experience with OSPF |
| | RFC 1587 OSPF NSSA |
| | RFC 1765 OSPF Database Overflow |
| | RFC 1850 OSPFv2 Management Information Base (MIB), traps |
| | RFC 2328 OSPFv2 |
| | RFC 2370 OSPF Opaque LSA Option |
| | RFC 3101 OSPF NSSA |
| | QoS/CoS |
| | IEEE 802.1P (CoS) |

Accessory Product Details

(RSVP) -
Version 1 Functional Specification
RFC 2280 Routing Policy Specification
Language
(RPSL)
RFC 2284 EAP over LAN
RFC 2338 VRRP
RFC 2364 PPP Over AAL5
RFC 2374 An Aggregatable Global Unicast
Address Format
RFC 2451 The ESP CBC-Mode Cipher
Algorithms
RFC 2453 RIPv2
RFC 2510 Internet X.509 Public Key
Infrastructure
Certificate Management Protocols
RFC 2511 Internet X.509 Certificate Request
Message Format
RFC 2516 A Method for Transmitting PPP Over
Ethernet (PPPoE)
RFC 2644 Directed Broadcast Control
RFC 2661 L2TP
RFC 2663 NAT Terminology and Considerations
RFC 2684 Multiprotocol Encapsulation over
ATM
Adaptation Layer 5
RFC 2694 DNS extensions to Network Address
Translators (DNS_ALG)
RFC 2702 Requirements for Traffic Engineering
Over MPLS
RFC 2747 RSVP Cryptographic Authentication
RFC 2763 Dynamic Name-to-System ID
mapping
support
RFC 2765 Stateless IP/ICMP Translation
Algorithm
(SIIT)
RFC 2766 Network Address Translation -
Protocol
Translation (NAT-PT)
RFC 2784 Generic Routing Encapsulation
(GRE)
RFC 2787 Definitions of Managed Objects for
VRRP
RFC 2961 RSVP Refresh Overhead Reduction
Extensions
RFC 2966 Domain-wide Prefix Distribution with
Two-Level IS-IS
RFC 2973 IS-IS Mesh Groups
RFC 2993 Architectural Implications of NAT
RFC 3022 Traditional IP Network Address
Translator (Traditional NAT)
RFC 3027 Protocol Complications with the IP
Network Address Translator
RFC 3031 Multiprotocol Label Switching
Architecture

RFC 2474 DS Field in the IPv4 and IPv6
Headers
RFC 2475 DiffServ Architecture
RFC 2597 DiffServ Assured Forwarding (AF)
RFC 2598 DiffServ Expedited Forwarding (EF)
RFC 3168 The Addition of Explicit Congestion
Notification (ECN) to IP

Security

IEEE 802.1X Port Based Network Access
Control
RFC 1321 The MD5 Message-Digest Algorithm
RFC 2082 RIP-2 MD5 Authentication
RFC 2104 Keyed-Hashing for Message
Authentication
RFC 2138 RADIUS Authentication
RFC 2209 RSVP-Message Processing
RFC 2246 Transport Layer Security (TLS)
RFC 2716 PPP EAP TLS Authentication
Protocol
RFC 2865 RADIUS Authentication
RFC 2866 RADIUS Accounting
RFC 3567 Intermediate System (IS) to IS
Cryptographic Authentication

VPN

RFC 2403 - HMAC-MD5-96
RFC 2404 - HMAC-SHA1-96
RFC 2405 - DES-CBC Cipher algorithm
RFC 2547 BGP/MPLS VPNs
RFC 2796 BGP Route Reflection - An
Alternative to
Full Mesh IBGP
RFC 2842 Capabilities Advertisement with BGP-
4
RFC 2858 Multiprotocol Extensions for BGP-4
RFC 2918 Route Refresh Capability for BGP-4
RFC 3107 Carrying Label Information in BGP-4

IPsec

RFC 1828 IP Authentication using Keyed MD5
RFC 2401 IP Security Architecture
RFC 2402 IP Authentication Header
RFC 2406 IP Encapsulating Security Payload
RFC 2407 - Domain of interpretation
RFC 2410 - The NULL Encryption Algorithm and
its
use with IPsec
RFC 2411 IP Security Document Roadmap
RFC 2412 - OAKLEY
RFC 2865 - Remote Authentication Dial In User
Service (RADIUS)

Accessory Product Details

HP A-MSR30-60 Multi-Service Router (JF230A)

| | |
|-----------------------------------|--|
| Ports | 4 SIC slots 6 MIM module slots 2 1000Base-T ports (IEEE 802.3ab Type 1000Base-T) 2 fixed Gigabit Ethernet SFP ports |
| Physical characteristics | Dimensions 16.61(d) x 17.4(w) x 5.2(h) in. (42.18 x 44.2 x 13.2 cm) (3U height) Weight 29.98 lb. (13.6 kg) |
| Memory and processor | Processor RISC @ 533 MHz, 256 MB DDR SDRAM, 256 MB compact flash |
| Mounting | Mounts in an EIA standard 19-in. rack |
| Performance | Throughput 360 Kpps (64-byte packets) Routing table size 30,000 entries |
| Environment | Operating temperature 32°F to 104°F (0°C to 40°C) Operating relative humidity 5% to 90%, non-condensing Non-operating/Storage temperature -40°F to 158°F (-40°C to 70°C) Non-operating/Storage relative humidity 5% to 90%, non-condensing |
| Electrical characteristics | Maximum heat dissipation 717 BTU/hr (756.44 kJ/hr) Voltage 100-120 / 200-240 VAC Maximum power rating 210 W Frequency 50 / 60 Hz Notes Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. |
| Safety | UL 60950-1; AS/NZS 60950; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1-03; EN 60950-1/A11; FDA 21 CFR Subchapter J |
| Emissions | EN 55022 Class A; ICES-003 Class A; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; AS/NZS CISPR22 Class A; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A; EN 55024:1998+ A1:2001 + A2:2003; EN 61000-4-11:2004; EN 61000-4-8:2001 |
| Telecom Management | FCC part 68 IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager; Telnet; RMON1; FTP; IEEE 802.3 Ethernet MIB |
| Services | 3-year, parts only, global next-day advance exchange (UX150E) 3-year, 4-hour onsite, 13x5 coverage for hardware (UX151E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UX154E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UX157E) 3-year, 24x7 SW phone support, software updates (UX160E) 4-year, 4-hour onsite, 13x5 coverage for hardware (UX152E) 4-year, 4-hour onsite, 24x7 coverage for hardware (UX155E) 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UX158E) 4-year, 24x7 SW phone support, software updates (UX161E) 5-year, 4-hour onsite, 13x5 coverage for hardware (UX153E) 5-year, 4-hour onsite, 24x7 coverage for hardware (UX156E) 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UX159E) 5-year, 24x7 SW phone support, software updates (UX162E) 3 Yr 6 hr Call-to-Repair Onsite (UX163E) |

Accessory Product Details

4 Yr 6 hr Call-to-Repair Onsite (UX164E)
5 Yr 6 hr Call-to-Repair Onsite (UX165E)

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Standards and protocols

(applies to all products in series)

BGP

RFC 1163 Border Gateway Protocol (BGP)
RFC 1267 Border Gateway Protocol 3 (BGP-3)
RFC 1657 Definitions of Managed Objects for BGPv4
RFC 1771 BGPv4
RFC 1772 Application of the BGP
RFC 1773 Experience with the BGP-4 Protocol
RFC 1774 BGP-4 Protocol Analysis
RFC 1965 BGP4 confederations
RFC 1997 BGP Communities Attribute
RFC 1998 PPP Gandalf FZA Compression Protocol
RFC 2385 BGP Session Protection via TCP MD5
RFC 2439 BGP Route Flap Damping

Device management

RFC 1305 NTPv3
RFC 1945 Hypertext Transfer Protocol -- HTTP/1.0
RFC 2271 FrameWork
RFC 2452 MIB for TCP6
RFC 2454 MIB for UDP6

General protocols

IEEE 802.1D MAC Bridges
IEEE 802.1p Priority
IEEE 802.1Q VLANs
IEEE 802.1s Multiple Spanning Trees
IEEE 802.1w Rapid Reconfiguration of Spanning Tree
RFC 768 UDP
RFC 783 TFTP Protocol (revision 2)
RFC 791 IP
RFC 792 ICMP
RFC 793 TCP
RFC 826 ARP
RFC 854 TELNET
RFC 855 Telnet Option Specification
RFC 856 TELNET
RFC 858 Telnet Suppress Go Ahead Option
RFC 894 IP over Ethernet
RFC 925 Multi-LAN Address Resolution
RFC 950 Internet Standard Subnetting Procedure
RFC 959 File Transfer Protocol (FTP)
RFC 1006 ISO transport services on top of the TCP:
Version 3
RFC 1027 Proxy ARP

RFC 3032 MPLS Label Stack Encoding
RFC 3036 LDP Specification
RFC 3046 DHCP Relay Agent Information Option
RFC 3063 MPLS Loop Prevention Mechanism
RFC 3065 Support AS confederation
RFC 3137 OSPF Stub Router Advertisement
RFC 3209 RSVP-TE Extensions to RSVP for LSP Tunnels
RFC 3210 Applicability Statement for Extensions to RSVP for LSP-Tunnels
RFC 3212 Constraint-Based LSP setup using LDP (CR-LDP)
RFC 3214 LSP Modification Using CR-LDP
RFC 3215 LDP State Machine
RFC 3246 Expedited Forwarding PHB
RFC 3268 Advanced Encryption Standard (AES) Ciphersuites for Transport Layer Security (TLS)
RFC 3277 IS-IS Transient Blackhole Avoidance
RFC 3279 Algorithms and Identifiers for the Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
RFC 3280 Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
RFC 3392 Support BGP capabilities advertisement
RFC 3479 Fault Tolerance for the Label Distribution Protocol (LDP)
RFC 3564 Requirements for Support of Differentiated Services-aware MPLS Traffic Engineering
RFC 3602 The AES-CBC Cipher Algorithm and Its Use with IPsec
RFC 3706 A Traffic-Based Method of Detecting Dead Internet Key Exchange (IKE) Peers
RFC 3784 ISIS TE support
RFC 3786 Extending the Number of IS-IS LSP Fragments Beyond the 256 Limit
RFC 3811 Definitions of Textual Conventions (TCs) for Multiprotocol Label Switching (MPLS) Management
RFC 3812 Multiprotocol Label Switching (MPLS)

Accessory Product Details

| | |
|--|--|
| RFC 1034 Domain Concepts and Facilities | Traffic Engineering (TE) Management Information Base (MIB) |
| RFC 1035 Domain Implementation and Specification | RFC 3847 Restart signaling for IS-IS |
| RFC 1042 IP Datagrams | |
| RFC 1058 RIPv1 | |
| RFC 1071 Computing the Internet Checksum | IP multicast |
| RFC 1091 Telnet Terminal-Type Option | RFC 1112 IGMP |
| RFC 1122 Host Requirements | RFC 2236 IGMPv2 |
| RFC 1141 Incremental updating of the Internet checksum | RFC 2283 Multiprotocol Extensions for BGP-4 |
| RFC 1142 OSI IS-IS Intra-domain Routing Protocol | RFC 2362 PIM Sparse Mode |
| RFC 1144 Compressing TCP/IP headers for low-speed serial links | RFC 2934 Protocol Independent Multicast MIB for IPv4 |
| RFC 1195 OSI ISIS for IP and Dual Environments | RFC 3376 IGMPv3 |
| RFC 1256 ICMP Router Discovery Protocol (IRDP) | |
| RFC 1293 Inverse Address Resolution Protocol | IPv6 |
| RFC 1315 Management Information Base for Frame Relay DTEs | RFC 1981 IPv6 Path MTU Discovery |
| RFC 1332 The PPP Internet Protocol Control Protocol (IPCP) | RFC 2080 RIPng for IPv6 |
| RFC 1333 PPP Link Quality Monitoring | RFC 2292 Advanced Sockets API for IPv6 |
| RFC 1334 PPP Authentication Protocols (PAP) | RFC 2373 IPv6 Addressing Architecture |
| RFC 1349 Type of Service | RFC 2460 IPv6 Specification |
| RFC 1350 TFTP Protocol (revision 2) | RFC 2461 IPv6 Neighbor Discovery |
| RFC 1377 The PPP OSI Network Layer Control Protocol (OSINLCP) | RFC 2462 IPv6 Stateless Address Auto-configuration |
| RFC 1381 SNMP MIB Extension for X.25 LAPB | RFC 2464 Transmission of IPv6 over Ethernet Networks |
| RFC 1471 The Definitions of Managed Objects for the Link Control Protocol of the Point-to-Point Protocol | RFC 2472 IP Version 6 over PPP |
| RFC 1472 The Definitions of Managed Objects for the Security Protocols of the Point-to-Point Protocol | RFC 2473 Generic Packet Tunneling in IPv6 |
| RFC 1490 Multiprotocol Interconnect over Frame Relay | RFC 2529 Transmission of IPv6 Packets over IPv4 |
| RFC 1519 CIDR | RFC 2545 Use of MP-BGP-4 for IPv6 |
| RFC 1534 DHCP/BOOTP Interoperation | RFC 2553 Basic Socket Interface Extensions for IPv6 |
| RFC 1542 Clarifications and Extensions for the Bootstrap Protocol | RFC 2740 OSPFv3 for IPv6 |
| RFC 1552 The PPP Internetworking Packet Exchange Control Protocol (IPXCP) | RFC 2893 Transition Mechanisms for IPv6 Hosts and Routers |
| RFC 1577 Classical IP and ARP over ATM | RFC 3056 Connection of IPv6 Domains via IPv4 Clouds |
| RFC 1613 Cisco Systems X.25 over TCP (XOT) | RFC 3513 IPv6 Addressing Architecture |
| RFC 1624 Incremental Internet Checksum | RFC 3596 DNS Extension for IPv6 |
| RFC 1631 NAT | |
| RFC 1638 PPP Bridging Control Protocol (BCP) | MIBs |
| RFC 1661 The Point-to-Point Protocol (PPP) | RFC 1213 MIB II |
| RFC 1662 PPP in HDLC-like Framing | RFC 1229 Interface MIB Extensions |
| RFC 1695 Definitions of Managed Objects for | RFC 1286 Bridge MIB |
| | RFC 1493 Bridge MIB |
| | RFC 1573 SNMP MIB II |
| | RFC 1724 RIPv2 MIB |
| | RFC 1757 Remote Network Monitoring MIB |
| | RFC 1850 OSPFv2 MIB |
| | RFC 2011 SNMPv2 MIB for IP |
| | RFC 2012 SNMPv2 MIB for TCP |
| | RFC 2013 SNMPv2 MIB for UDP |
| | RFC 2233 Interfaces MIB |
| | RFC 2454 IPV6-UDP-MIB |
| | RFC 2465 IPv6 MIB |
| | RFC 2466 ICMPv6 MIB |

Accessory Product Details

| | |
|--|---|
| ATM Management Version 8.0 using SMIv2 | RFC 2618 RADIUS Client MIB |
| RFC 1701 Generic Routing Encapsulation | RFC 2620 RADIUS Accounting MIB |
| RFC 1702 Generic Routing Encapsulation over IPv4 networks | RFC 2674 802.1p and IEEE 802.1Q Bridge MIB |
| RFC 1721 RIP-2 Analysis | RFC 2737 Entity MIB (Version 2) |
| RFC 1722 RIP-2 Applicability | RFC 2863 The Interfaces Group MIB |
| RFC 1723 RIP v2 | RFC 2933 IGMP MIB |
| RFC 1795 Data Link Switching: Switch-to-Switch Protocol AIW DLSw RIG: DLSw Closed Pages, DLSw Standard Version 1 | RFC 3813 MPLS LSR MIB |
| RFC 1812 IPv4 Routing | Network management |
| RFC 1829 The ESP DES-CBC Transform | IEEE 802.1D (STP) |
| RFC 1877 PPP Internet Protocol Control Protocol | RFC 1155 Structure of Management Information |
| Extensions for Name Server Addresses | RFC 1157 SNMPv1 |
| RFC 1944 Benchmarking Methodology for Network Interconnect Devices | RFC 1905 SNMPv2 Protocol Operations |
| RFC 1973 PPP in Frame Relay | RFC 2272 SNMPv3 Management Protocol |
| RFC 1974 PPP Stac LZS Compression Protocol | RFC 2273 SNMPv3 Applications |
| RFC 1990 The PPP Multilink Protocol (MP) | RFC 2274 USM for SNMPv3 |
| RFC 1994 PPP Challenge Handshake Authentication Protocol (CHAP) | RFC 2275 VACM for SNMPv3 |
| RFC 2091 Trigger RIP | RFC 2575 SNMPv3 View-based Access Control Model (VACM) |
| RFC 2131 DHCP | RFC 3164 BSD syslog Protocol |
| RFC 2132 DHCP Options and BOOTP Vendor Extensions | OSPF |
| RFC 2166 APPN Implementer's Workshop Closed Pages Document DLSw v2.0 Enhancements | RFC 1245 OSPF protocol analysis |
| RFC 2205 Resource ReSerVation Protocol (RSVP) - Version 1 Functional Specification | RFC 1246 Experience with OSPF |
| RFC 2280 Routing Policy Specification Language (RPSL) | RFC 1587 OSPF NSSA |
| RFC 2284 EAP over LAN | RFC 1765 OSPF Database Overflow |
| RFC 2338 VRRP | RFC 1850 OSPFv2 Management Information Base (MIB), traps |
| RFC 2364 PPP Over AAL5 | RFC 2328 OSPFv2 |
| RFC 2374 An Aggregatable Global Unicast Address Format | RFC 2370 OSPF Opaque LSA Option |
| RFC 2451 The ESP CBC-Mode Cipher Algorithms | RFC 3101 OSPF NSSA |
| RFC 2453 IPv6 | QoS/CoS |
| RFC 2510 Internet X.509 Public Key Infrastructure Certificate Management Protocols | IEEE 802.1P (CoS) |
| RFC 2511 Internet X.509 Certificate Request Message Format | RFC 2474 DS Field in the IPv4 and IPv6 Headers |
| RFC 2516 A Method for Transmitting PPP Over Ethernet (PPPoE) | RFC 2475 DiffServ Architecture |
| RFC 2644 Directed Broadcast Control | RFC 2597 DiffServ Assured Forwarding (AF) |
| RFC 2661 L2TP | RFC 2598 DiffServ Expedited Forwarding (EF) |
| RFC 2663 NAT Terminology and Considerations | RFC 3168 The Addition of Explicit Congestion Notification (ECN) to IP |
| | Security |
| | IEEE 802.1X Port Based Network Access Control |
| | RFC 1321 The MD5 Message-Digest Algorithm |
| | RFC 2082 RIP-2 MD5 Authentication |
| | RFC 2104 Keyed-Hashing for Message Authentication |
| | RFC 2138 RADIUS Authentication |
| | RFC 2209 RSVP-Message Processing |
| | RFC 2246 Transport Layer Security (TLS) |
| | RFC 2716 PPP EAP TLS Authentication Protocol |
| | RFC 2865 RADIUS Authentication |
| | RFC 2866 RADIUS Accounting |
| | RFC 3567 Intermediate System (IS) to IS |

Accessory Product Details

| | |
|--|--|
| RFC 2684 Multiprotocol Encapsulation over ATM | Cryptographic Authentication |
| Adaptation Layer 5 | VPN |
| RFC 2694 DNS extensions to Network Address Translators (DNS_ALG) | RFC 2403 - HMAC-MD5-96 |
| RFC 2702 Requirements for Traffic Engineering Over MPLS | RFC 2404 - HMAC-SHA1-96 |
| RFC 2747 RSVP Cryptographic Authentication | RFC 2405 - DES-CBC Cipher algorithm |
| RFC 2763 Dynamic Name-to-System ID mapping support | RFC 2547 BGP/MPLS VPNs |
| RFC 2765 Stateless IP/ICMP Translation Algorithm (SIIT) | RFC 2796 BGP Route Reflection - An Alternative to Full Mesh IBGP |
| RFC 2766 Network Address Translation - Protocol Translation (NAT-PT) | RFC 2842 Capabilities Advertisement with BGP-4 |
| RFC 2784 Generic Routing Encapsulation (GRE) | RFC 2858 Multiprotocol Extensions for BGP-4 |
| RFC 2787 Definitions of Managed Objects for VRRP | RFC 2918 Route Refresh Capability for BGP-4 |
| RFC 2961 RSVP Refresh Overhead Reduction Extensions | RFC 3107 Carrying Label Information in BGP-4 |
| RFC 2966 Domain-wide Prefix Distribution with Two-Level IS-IS | IPsec |
| RFC 2973 IS-IS Mesh Groups | RFC 1828 IP Authentication using Keyed MD5 |
| RFC 2993 Architectural Implications of NAT | RFC 2401 IP Security Architecture |
| RFC 3022 Traditional IP Network Address Translator (Traditional NAT) | RFC 2402 IP Authentication Header |
| RFC 3027 Protocol Complications with the IP Network Address Translator | RFC 2406 IP Encapsulating Security Payload |
| RFC 3031 Multiprotocol Label Switching Architecture | RFC 2407 - Domain of interpretation |
| | RFC 2410 - The NULL Encryption Algorithm and its use with IPsec |
| | RFC 2411 IP Security Document Roadmap |
| | RFC 2412 – OAKLEY |
| | RFC 2865 - Remote Authentication Dial In User Service (RADIUS) |

HP A-MSR30-60 PoE Multi-Service Router (JF804A)

| | |
|---------------------------------|--|
| Ports | 4 SIC slots |
| | 6 MIM module slots |
| | 2 1000Base-T ports (IEEE 802.3ab Type 1000Base-T) |
| | 2 fixed Gigabit Ethernet SFP ports |
| Physical characteristics | Dimensions 16.61(d) x 17.4(w) x 5.2(h) in. (42.18 x 44.2 x 13.2 cm) (3U height) |
| | Weight 29.98 lb. (13.6 kg) |
| Memory and processor | Processor RISC @ 533 MHz, 256 MB DDR SDRAM, 256 MB compact flash |
| Mounting | Mounts in an EIA standard 19-in. rack |
| Performance | Throughput 360 Kpps (64-byte packets) |
| | Routing table size 30,000 entries |
| Environment | Operating temperature 32°F to 104°F (0°C to 40°C) |
| | Operating relative humidity 5% to 90%, non-condensing |
| | Non-operating/Storage temperature -40°F to 158°F (-40°C to 70°C) |
| | Non-operating/Storage relative humidity 5% to 90%, non-condensing |
| Electrical | Maximum heat 717 BTU/hr (756.44 kJ/hr) |

Accessory Product Details

| | |
|---|--|
| characteristics | dissipation Voltage 100-120 / 200-240 VAC Maximum power rating 210 W PoE power 375 W Frequency 50 / 60 Hz Notes Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. PoE power is the power supplied by the internal power supply. It is dependent on the type and quantity of power supplies and may be supplemented with the use of an external power supply (EPS). |
| Safety | UL 60950-1; AS/NZS 60950; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1-03; EN 60950-1/A11; FDA 21 CFR Subchapter J |
| Emissions | EN 55022 Class A; ICES-003 Class A; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; AS/NZS CISPR22 Class A; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A; EN 55024:1998+ A1:2001 + A2:2003; EN 61000-4-11:2004; EN 61000-4-8:2001 |
| Telecom Management | FCC part 68 IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager; Telnet; RMON1; FTP; IEEE 802.3 Ethernet MIB |
| Services | 3-year, parts only, global next-day advance exchange (UX150E) 3-year, 4-hour onsite, 13x5 coverage for hardware (UX151E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UX154E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UX157E) 3-year, 24x7 SW phone support, software updates (UX160E) 4-year, 4-hour onsite, 13x5 coverage for hardware (UX152E) 4-year, 4-hour onsite, 24x7 coverage for hardware (UX155E) 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UX158E) 4-year, 24x7 SW phone support, software updates (UX161E) 5-year, 4-hour onsite, 13x5 coverage for hardware (UX153E) 5-year, 4-hour onsite, 24x7 coverage for hardware (UX156E) 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UX159E) 5-year, 24x7 SW phone support, software updates (UX162E) 3 Yr 6 hr Call-to-Repair Onsite (UX163E) 4 Yr 6 hr Call-to-Repair Onsite (UX164E) 5 Yr 6 hr Call-to-Repair Onsite (UX165E) |
| | Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office. |
| Standards and protocols (applies to all products in series) | BGP RFC 1163 Border Gateway Protocol (BGP) RFC 1267 Border Gateway Protocol 3 (BGP-3) RFC 1657 Definitions of Managed Objects for BGPv4 RFC 1771 BGPv4 RFC 1772 Application of the BGP RFC 1773 Experience with the BGP-4 Protocol RFC 1774 BGP-4 Protocol Analysis RFC 1965 BGP4 confederations RFC 1997 BGP Communities Attribute RFC 1998 PPP Gandalf FZA Compression |
| | RFC 3032 MPLS Label Stack Encoding RFC 3036 LDP Specification RFC 3046 DHCP Relay Agent Information Option RFC 3063 MPLS Loop Prevention Mechanism RFC 3065 Support AS confederation RFC 3137 OSPF Stub Router Advertisement RFC 3209 RSVP-TE Extensions to RSVP for LSP Tunnels RFC 3210 Applicability Statement for Extensions to |

Accessory Product Details

Protocol
RFC 2385 BGP Session Protection via TCP MD5
RFC 2439 BGP Route Flap Damping

Device management

RFC 1305 NTPv3
RFC 1945 Hypertext Transfer Protocol -- HTTP/1.0
RFC 2271 FrameWork
RFC 2452 MIB for TCP6
RFC 2454 MIB for UDP6

General protocols

IEEE 802.1D MAC Bridges
IEEE 802.1p Priority
IEEE 802.1Q VLANs
IEEE 802.1s Multiple Spanning Trees
IEEE 802.1w Rapid Reconfiguration of Spanning Tree
RFC 768 UDP
RFC 783 TFTP Protocol (revision 2)
RFC 791 IP
RFC 792 ICMP
RFC 793 TCP
RFC 826 ARP
RFC 854 TELNET
RFC 855 Telnet Option Specification
RFC 856 TELNET
RFC 858 Telnet Suppress Go Ahead Option
RFC 894 IP over Ethernet
RFC 925 Multi-LAN Address Resolution
RFC 950 Internet Standard Subnetting Procedure
RFC 959 File Transfer Protocol (FTP)
RFC 1006 ISO transport services on top of the TCP:
Version 3
RFC 1027 Proxy ARP
RFC 1034 Domain Concepts and Facilities
RFC 1035 Domain Implementation and Specification
RFC 1042 IP Datagrams
RFC 1058 RIPv1
RFC 1071 Computing the Internet Checksum
RFC 1091 Telnet Terminal-Type Option
RFC 1122 Host Requirements
RFC 1141 Incremental updating of the Internet checksum
RFC 1142 OSI IS-IS Intra-domain Routing Protocol
RFC 1144 Compressing TCP/IP headers for low-speed serial links
RFC 1195 OSI ISIS for IP and Dual Environments
RFC 1256 ICMP Router Discovery Protocol (IRDP)
RFC 1293 Inverse Address Resolution Protocol

RSVP for LSP-Tunnels
RFC 3212 Constraint-Based LSP setup using LDP
(CR-LDP)
RFC 3214 LSP Modification Using CR-LDP
RFC 3215 LDP State Machine
RFC 3246 Expedited Forwarding PHB
RFC 3268 Advanced Encryption Standard (AES) Ciphersuites for Transport Layer Security (TLS)
RFC 3277 IS-IS Transient Blackhole Avoidance
RFC 3279 Algorithms and Identifiers for the Internet
X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
RFC 3280 Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
RFC 3392 Support BGP capabilities advertisement
RFC 3479 Fault Tolerance for the Label Distribution Protocol (LDP)
RFC 3564 Requirements for Support of Differentiated Services-aware MPLS Traffic Engineering
RFC 3602 The AES-CBC Cipher Algorithm and Its Use with IPsec
RFC 3706 A Traffic-Based Method of Detecting Dead Internet Key Exchange (IKE) Peers
RFC 3784 ISIS TE support
RFC 3786 Extending the Number of IS-IS LSP Fragments Beyond the 256 Limit
RFC 3811 Definitions of Textual Conventions (TCs) for Multiprotocol Label Switching (MPLS) Management
RFC 3812 Multiprotocol Label Switching (MPLS) Traffic Engineering (TE) Management Information Base (MIB)
RFC 3847 Restart signaling for IS-IS

IP multicast

RFC 1112 IGMP
RFC 2236 IGMPv2
RFC 2283 Multiprotocol Extensions for BGP-4
RFC 2362 PIM Sparse Mode
RFC 2934 Protocol Independent Multicast MIB for IPv4
RFC 3376 IGMPv3

IPv6

RFC 1981 IPv6 Path MTU Discovery
RFC 2080 RIPng for IPv6
RFC 2292 Advanced Sockets API for IPv6

Accessory Product Details

- RFC 1315 Management Information Base for Frame Relay DTEs
- RFC 1332 The PPP Internet Protocol Control Protocol (IPCP)
- RFC 1333 PPP Link Quality Monitoring
- RFC 1334 PPP Authentication Protocols (PAP)
- RFC 1349 Type of Service
- RFC 1350 TFTP Protocol (revision 2)
- RFC 1377 The PPP OSI Network Layer Control Protocol (OSINLCP)
- RFC 1381 SNMP MIB Extension for X.25 LAPB
- RFC 1471 The Definitions of Managed Objects for the Link Control Protocol of the Point-to-Point Protocol
- RFC 1472 The Definitions of Managed Objects for the Security Protocols of the Point-to-Point Protocol
- RFC 1490 Multiprotocol Interconnect over Frame Relay
- RFC 1519 CIDR
- RFC 1534 DHCP/BOOTP Interoperation
- RFC 1542 Clarifications and Extensions for the Bootstrap Protocol
- RFC 1552 The PPP Internetworking Packet Exchange Control Protocol (IPXCP)
- RFC 1577 Classical IP and ARP over ATM
- RFC 1613 Cisco Systems X.25 over TCP (XOT)
- RFC 1624 Incremental Internet Checksum
- RFC 1631 NAT
- RFC 1638 PPP Bridging Control Protocol (BCP)
- RFC 1661 The Point-to-Point Protocol (PPP)
- RFC 1662 PPP in HDLC-like Framing
- RFC 1695 Definitions of Managed Objects for ATM Management Version 8.0 using SMIv2
- RFC 1701 Generic Routing Encapsulation
- RFC 1702 Generic Routing Encapsulation over IPv4 networks
- RFC 1721 RIP-2 Analysis
- RFC 1722 RIP-2 Applicability
- RFC 1723 RIP v2
- RFC 1795 Data Link Switching: Switch-to-Switch Protocol AIW DLSw RIG: DLSw Closed Pages, DLSw Standard Version 1
- RFC 1812 IPv4 Routing
- RFC 1829 The ESP DES-CBC Transform
- RFC 1877 PPP Internet Protocol Control Protocol Extensions for Name Server Addresses
- RFC 1944 Benchmarking Methodology for
- RFC 2373 IPv6 Addressing Architecture
- RFC 2460 IPv6 Specification
- RFC 2461 IPv6 Neighbor Discovery
- RFC 2462 IPv6 Stateless Address Auto-configuration
- RFC 2464 Transmission of IPv6 over Ethernet Networks
- RFC 2472 IP Version 6 over PPP
- RFC 2473 Generic Packet Tunneling in IPv6
- RFC 2529 Transmission of IPv6 Packets over IPv4
- RFC 2545 Use of MP-BGP-4 for IPv6
- RFC 2553 Basic Socket Interface Extensions for IPv6
- RFC 2740 OSPFv3 for IPv6
- RFC 2893 Transition Mechanisms for IPv6 Hosts and Routers
- RFC 3056 Connection of IPv6 Domains via IPv4 Clouds
- RFC 3513 IPv6 Addressing Architecture
- RFC 3596 DNS Extension for IPv6
- MIBs**
- RFC 1213 MIB II
- RFC 1229 Interface MIB Extensions
- RFC 1286 Bridge MIB
- RFC 1493 Bridge MIB
- RFC 1573 SNMP MIB II
- RFC 1724 RIPv2 MIB
- RFC 1757 Remote Network Monitoring MIB
- RFC 1850 OSPFv2 MIB
- RFC 2011 SNMPv2 MIB for IP
- RFC 2012 SNMPv2 MIB for TCP
- RFC 2013 SNMPv2 MIB for UDP
- RFC 2233 Interfaces MIB
- RFC 2454 IPV6-UDP-MIB
- RFC 2465 IPv6 MIB
- RFC 2466 ICMPv6 MIB
- RFC 2618 RADIUS Client MIB
- RFC 2620 RADIUS Accounting MIB
- RFC 2674 802.1p and IEEE 802.1Q Bridge MIB
- RFC 2737 Entity MIB (Version 2)
- RFC 2863 The Interfaces Group MIB
- RFC 2933 IGMP MIB
- RFC 3813 MPLS LSR MIB
- Network management**
- IEEE 802.1D (STP)
- RFC 1155 Structure of Management Information
- RFC 1157 SNMPv1
- RFC 1905 SNMPv2 Protocol Operations
- RFC 2272 SNMPv3 Management Protocol
- RFC 2273 SNMPv3 Applications
- RFC 2274 USM for SNMPv3
- RFC 2275 VACM for SNMPv3
- RFC 2575 SNMPv3 View-based Access Control Model (VACM)

Accessory Product Details

| | |
|--|---|
| Network Interconnect Devices | RFC 3164 BSD syslog Protocol |
| RFC 1973 PPP in Frame Relay | OSPF |
| RFC 1974 PPP Stac LZS Compression Protocol | RFC 1245 OSPF protocol analysis |
| RFC 1990 The PPP Multilink Protocol (MP) | RFC 1246 Experience with OSPF |
| RFC 1994 PPP Challenge Handshake Authentication Protocol (CHAP) | RFC 1587 OSPF NSSA |
| RFC 2091 Trigger RIP | RFC 1765 OSPF Database Overflow |
| RFC 2131 DHCP | RFC 1850 OSPFv2 Management Information Base (MIB), traps |
| RFC 2132 DHCP Options and BOOTP Vendor Extensions | RFC 2328 OSPFv2 |
| RFC 2166 APPN Implementer's Workshop Closed | RFC 2370 OSPF Opaque LSA Option |
| Pages Document DLSw v2.0 Enhancements | RFC 3101 OSPF NSSA |
| RFC 2205 Resource ReSerVation Protocol (RSVP) - Version 1 Functional Specification | QoS/CoS |
| RFC 2280 Routing Policy Specification Language (RPSL) | IEEE 802.1P (CoS) |
| RFC 2284 EAP over LAN | RFC 2474 DS Field in the IPv4 and IPv6 Headers |
| RFC 2338 VRRP | RFC 2475 DiffServ Architecture |
| RFC 2364 PPP Over AAL5 | RFC 2597 DiffServ Assured Forwarding (AF) |
| RFC 2374 An Aggregatable Global Unicast Address Format | RFC 2598 DiffServ Expedited Forwarding (EF) |
| RFC 2451 The ESP CBC-Mode Cipher Algorithms | RFC 3168 The Addition of Explicit Congestion Notification (ECN) to IP |
| RFC 2453 RIPv2 | Security |
| RFC 2510 Internet X.509 Public Key Infrastructure | IEEE 802.1X Port Based Network Access Control |
| Certificate Management Protocols | RFC 1321 The MD5 Message-Digest Algorithm |
| RFC 2511 Internet X.509 Certificate Request Message Format | RFC 2082 RIP-2 MD5 Authentication |
| RFC 2516 A Method for Transmitting PPP Over Ethernet (PPPoE) | RFC 2104 Keyed-Hashing for Message Authentication |
| RFC 2644 Directed Broadcast Control | RFC 2138 RADIUS Authentication |
| RFC 2661 L2TP | RFC 2209 RSVP-Message Processing |
| RFC 2663 NAT Terminology and Considerations | RFC 2246 Transport Layer Security (TLS) |
| RFC 2684 Multiprotocol Encapsulation over ATM | RFC 2716 PPP EAP TLS Authentication Protocol |
| Adaptation Layer 5 | RFC 2865 RADIUS Authentication |
| RFC 2694 DNS extensions to Network Address Translators (DNS_ALG) | RFC 2866 RADIUS Accounting |
| RFC 2702 Requirements for Traffic Engineering Over MPLS | RFC 3567 Intermediate System (IS) to IS Cryptographic Authentication |
| RFC 2747 RSVP Cryptographic Authentication | VPN |
| RFC 2763 Dynamic Name-to-System ID mapping support | RFC 2403 - HMAC-MD5-96 |
| RFC 2765 Stateless IP/ICMP Translation Algorithm (SIIT) | RFC 2404 - HMAC-SHA1-96 |
| RFC 2766 Network Address Translation - Protocol Translation (NAT-PT) | RFC 2405 - DES-CBC Cipher algorithm |
| RFC 2784 Generic Routing Encapsulation (GRE) | RFC 2547 BGP/MPLS VPNs |
| | RFC 2796 BGP Route Reflection - An Alternative to Full Mesh IBGP |
| | RFC 2842 Capabilities Advertisement with BGP-4 |
| | RFC 2858 Multiprotocol Extensions for BGP-4 |
| | RFC 2918 Route Refresh Capability for BGP-4 |
| | RFC 3107 Carrying Label Information in BGP-4 |
| | IPsec |
| | RFC 1828 IP Authentication using Keyed MD5 |
| | RFC 2401 IP Security Architecture |

Accessory Product Details

| | |
|--|---|
| RFC 2787 Definitions of Managed Objects for VRRP | RFC 2402 IP Authentication Header |
| RFC 2961 RSVP Refresh Overhead Reduction Extensions | RFC 2406 IP Encapsulating Security Payload |
| RFC 2966 Domain-wide Prefix Distribution with Two-Level IS-IS | RFC 2407 - Domain of interpretation |
| RFC 2973 IS-IS Mesh Groups | RFC 2410 - The NULL Encryption Algorithm and its use with IPsec |
| RFC 2993 Architectural Implications of NAT | RFC 2411 IP Security Document Roadmap |
| RFC 3022 Traditional IP Network Address Translator (Traditional NAT) | RFC 2412 – OAKLEY |
| RFC 3027 Protocol Complications with the IP Network Address Translator | RFC 2865 - Remote Authentication Dial In User Service (RADIUS) |
| RFC 3031 Multiprotocol Label Switching Architecture | |

To learn more, visit www.hp.com/networking

© Copyright 2010-2011 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Intel and Celeron are trademarks of Intel Corporation in the U.S. and other countries. Microsoft is a U.S. registered trademark of Microsoft Corporation.